



Cisco Firepower 1000 Series Datasheet



Router-Switch.com
Leading Network Hardware Supplier

CONTENT

Content	1
Overview	2
Appearance	2
Key Features and Benefits	2
Series Models	4
Specification	5
Ordering Information	8
Where To Buy	8
Sources	8

Contact Us

Tel: +1-626-239-8066 (USA) / +852-3050-1066 / +852-3174-6166 /

Fax: +852-3050-1066 (Hong Kong)

Email: cisco@router-switch.com (Sales Inquiries)

ccie-support@router-switch.com (CCIE Technical Support)

Overview

The Cisco Firepower® 1000 Series is a family of three threat-focused Next-Generation Firewall (NGFW) security platforms that deliver business resiliency through superior threat defense. It offers exceptional sustained performance when advanced threat functions are enabled. The 1000 Series' throughput range addresses use cases from the small office, home office, remote branch office to the Internet edge. The 1000 Series platforms run Cisco Firepower Threat Defense (FTD). Support for Cisco® Adaptive Security Appliance (ASA) Firewall will be added in a later release. (Figure 1).

Appearance

Figure 1. Cisco Firepower® 1000 Series



Key Features and Benefits

Table 1. Performance specifications and feature highlights for Cisco Firepower 1000 with the Cisco Firepower Threat Defense image

Features	1010	1120	1140
Throughput: Firewall (FW) + Application Visibility and Control (AVC) (1024B)	650 Mbps	1.5 Gbps	2.2 Gbps

Throughput: FW + AVC + Intrusion Prevention System (IPS) (1024B)	650 Mbps	1.5 Gbps	2.2 Gbps
Maximum concurrent sessions, with AVC	100K	200K	400K
Maximum new connections per second, with AVC	6K	15K	22K
Transport Layer Security (TLS)	150 Mbps	700 Mbps	1 Gbps
Throughput: NGIPS (1024B)	650 Mbps	1.5 Gbps	2.2 Gbps
IPSec VPN throughput (1024B TCP w/Fastpath)	300 Mbps	1 Gbps	1.2 Gbps
Maximum VPN Peers	75	150	400
Cisco Firepower Device Manager (local management)	Yes	Yes	Yes
Centralized management	Centralized configuration, logging, monitoring, and reporting are performed by the Management Center or alternatively in the cloud with Cisco Defense Orchestrator		
AVC	Standard, supporting more than 4000 applications, as well as geolocations, users, and websites		
AVC: OpenAppID support for custom, open-source application detectors	Standard		
Cisco Security Intelligence	Standard, with IP, URL, and DNS threat intelligence		
Cisco Firepower NGIPS	Available; can passively detect endpoints and infrastructure for threat correlation and Indicators of Compromise (IoC) intelligence		
Cisco Advanced Malware Protection (AMP) for Networks	Available; enables detection, blocking, tracking, analysis, and containment of targeted and persistent malware, addressing the attack continuum both during and		

	after attacks. Integrated threat correlation with Cisco AMP for Endpoints is also optionally available.
Cisco AMP Threat Grid sandboxing	Available
URL filtering: number of categories	More than 80
URL filtering: number of URLs categorized	More than 280 million
Automated threat feed and IPS signature updates	Yes: class-leading Collective Security Intelligence (CSI) from the Cisco Talos® group
Third-party and open-source ecosystem	Open API for integrations with third-party products; Snort® and OpenAppID community resources for new and specific threats
High availability and clustering	Active/standby
Cisco Trust Anchor Technologies	Cisco Firepower 1000 Series platforms include Trust Anchor Technologies for supply chain and software image assurance. Please see the section below for additional details.
<p>NOTE: Performance will vary depending on features activated, and network traffic protocol mix, and packet size characteristics. Performance is subject to change with new software releases. Consult your Cisco representative for detailed sizing guidance.</p>	

Series Models

Table 2. The Cisco Firepower 1000 Series provides 3 platforms.

Model	NGFW	Next-Generation Intrusion Prevention System (NGIPS)	Interfaces
FPR-1010	650 Mbps	650 Mbps	8 x RJ45
FPR-1120	1.5 Gbps	1.5 Gbps	8 x RJ45, 4 x SFP
FPR-1140	2.2 Gbps	2.2 Gbps	8 x RJ45, 4 x SFP

Table 3. Specification of Cisco Firepower 1000 Series.

Features	1010	1120	1140
Dimensions (H x W x D)	1.82 x 7.85 x 8.07 in.	1.72 x 17.2 x 10.58 in.	1.72 x 17.2 x 10.58 in.
Form factor (rack units)	DT	1RU	1RU
Integrated I/O	8 x RJ-45	8 x RJ-45, 4 x SFP	8 x RJ-45, 4 x SFP
Integrated network management ports	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)
Serial port	1 x RJ-45 console	1 x RJ-45 console	1 x RJ-45 console
USB	1 x USB 3.0 Type-A (500mA)	1 x USB 3.0 Type-A (500mA)	1 x USB 3.0 Type-A (500mA)
Storage	1 x 200 GB	1 x 200 GB	1 x 200 GB
Power supply configuration	+12V and -53.5V	+12V	+12V
AC input voltage	100 to 240V AC	100 to 240V AC	100 to 240V AC
AC maximum input current	< 2A at 100V, < 1A at 240V	< 2A at 100V, < 1A at 240V	< 2A at 100V, < 1A at 240V
AC maximum output power	115W (55W of +12V and 60W of -53.5V)	100W	100W
AC frequency	50 to 60 Hz	50 to 60 Hz	50 to 60 Hz
AC efficiency	>88% at 50% load	>85% at 50% load	>85% at 50% load
Redundancy	None	None	None

Fans	None	1 integrated fan	1 integrated fan
Noise	0 dBA	31.7 dBA @ 25C, 56.8 dBA at highest system performance	34.2 dBA @ 25C, 56.8 dBA at highest system performance
Rack mountable	Yes. Separate kit must be ordered.	Yes. Fixed mount brackets included (2-post).	Yes. Fixed mount brackets included (2-post).
Weight	3 lb (1.36 kg)	8 lb (3.63 kg)	8 lb (3.63 kg)
Temperature: operating	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)
Temperature: nonoperating	-13 to 158°F (-25 to 70°C)	-13 to 158°F (-25 to 70°C)	-13 to 158°F (-25 to 70°C)
Humidity: operating	90% noncondensing	90% noncondensing	90% noncondensing
Humidity: nonoperating	10 to 90% noncondensing	10 to 90% noncondensing	10 to 90% noncondensing
Altitude: operating	9843 ft (max) 3000 m (max)	9843 ft (max) 3000 m (max)	9843 ft (max) 3000 m (max)
Altitude: nonoperating	15,000 ft (max)	15,000 ft (max)	15,000 ft (max)

Table 4. Cisco Firepower 1000 Series regulatory, safety, and EMC compliance

Specification	Description
Regulatory compliance	Products comply with CE markings per directives 2004/108/EC and 2006/108/EC
Safety	<ul style="list-style-type: none"> ● UL 60950-1 ● CAN/CSA-C22.2 No. 60950-1 ● EN 60950-1

	<ul style="list-style-type: none"> ● IEC 60950-1 ● AS/NZS 60950-1 ● GB4943
EMC: emissions	<ul style="list-style-type: none"> ● 47CFR Part 15 (CFR 47) Class A (FCC Class A) ● AS/NZS CISPR22 Class A ● CISPR22 CLASS A ● EN55022 Class A ● ICES003 Class A ● VCCI Class A ● EN61000-3-2 ● EN61000-3-3 ● KN22 Class A ● CNS13438 Class A ● EN300386 ● TCVN7189
EMC: immunity	<ul style="list-style-type: none"> ● EN55024 ● CISPR24 ● EN300386 ● KN24 ● TVCN 7317 ● EN-61000-4-2, EN-61000-4-3, EN-61000-4-4, EN-61000-4-5, EN-61000-4-6, EN-61000-4-8, EN61000-4-11

Ordering Information

Table 5. Cisco FirePower 1000 series options.

SKU	Description
FPR1010-NGFW-K9	Cisco Firepower 1010 NGFW Appliance, Desktop
FPR1120-NGFW-K9	Cisco Firepower 1120 NGFW Appliance, 1U
FPR1140-NGFW-K9	Cisco Firepower 1140 NGFW Appliance, 1U

Where To Buy

Want to buy this series of products? please contact:

- Tel: +1-626-239-8066 (USA)/ +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com (Sales Inquiries)

Or visit: [Cisco FirePower 1000 Series](#)

About us

Router-switch.com, founded in 2002, is one of the biggest Global Network Hardware Supplier. We are a leading provider of network products with 14,500+ customers in over 200 countries. We provide original new and used network equipments (Cisco, Huawei, HPE, Dell, Fortinet, Hikvision, Juniper, EMC, etc.), including Routers, Switches, Servers, Storage, Telepresence and Videoconferencing, IP Phones, Firewalls, Wireless APs & Controllers, EHWIC/HWIC/VWIC Cards, SFPs, Memory & Flash, Hard Disk, Cables, and all kinds of network solutions related products.

Sources

<https://www.cisco.com/c/en/us/products/collateral/security/firepower-1000-series/datasheet-c78-742469.html>