



Aruba 2930F Switch Series Data Sheet



Router-Switch.com
Leading Network Hardware Supplier

CONTENT

Content	1
Overview	2
Specifications	3
Accessories.....	30
Ordering information	31
Where to Buy	32
Sources	32

Contact Us

Tel: +1-626-239-8066 (USA) / +852-3050-1066 / +852-3174-6166

Fax: +852-3050-1066 (Hong Kong)

Email: sales@router-switch.com (Sales Inquiries)

OVERVIEW

The [Aruba 2930F Switch Series](#) is designed for customers creating digital workplaces that are optimized for mobile users with an integrated wired and wireless approach. These Layer 3 access switches are easy to deploy and manage with advanced security and network management tools like Aruba ClearPass Policy Manager and Aruba AirWave. With support from Aruba Central, you can quickly set up remote branch sites with little or no IT support. A powerful Aruba ProVision ASIC delivers performance and flexibility to meet the needs of today and tomorrow's network programmability and automation requirements. Stacking with Virtual Switching Framework (VSF) provides simplicity and scalability. The 2930F supports built-in 1GbE or 10GbE uplinks, PoE+, Access OSPF routing, Dynamic Segmentation, robust QoS, RIP routing, and IPv6 with no software licensing required.



The Aruba 2930F Switch Series provides a convenient and cost-effective access switch solution that can be quickly set up with Zero Touch Provisioning and built-in 10GbE uplinks. The robust Layer 3 feature set includes a limited lifetime warranty.

Key Features

- Aruba Layer 3 switch series with VSF stacking, static, Rip and Access OSPF Routing, Dynamic Segmentation, ACLs, and robust QoS
- Consistent wired/wireless experience with Aruba AirWave and Aruba ClearPass Policy Manager
- Convenient built-in 1GbE or 10GbE uplinks and up to 740 W PoE+
- Ready for the software defined network with REST APIs and OpenFlow support
- Simple deployment with Zero Touch Provisioning and cloud-based Aruba Central support

Models

Aruba 2930F 24G 4SFP+ Switch	JL253A
Aruba 2930F 48G 4SFP+ Switch	JL254A
Aruba 2930F 24G PoE+ 4SFP+ Switch	JL255A
Aruba 2930F 48G PoE+ 4SFP+ Switch	JL256A

Aruba 2930F 8G PoE+ 2SFP+ Switch	JL258A
Aruba 2930F 24G 4SFP Switch	JL259A
Aruba 2930F 48G 4SFP Switch	JL260A
Aruba 2930F 24G PoE+ 4SFP Switch	JL261A
Aruba 2930F 48G PoE+ 4SFP Switch	JL262A
Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch	JL263A
Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch	JL264A
Aruba 2930F 48G PoE+ 4SFP 740W Switch	JL557A
Aruba 2930F 48G PoE+ 4SFP+ 740W Switch	JL558A
Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch	JL559A

SPECIFICATIONS

These tables shows models of Aruba 2930F series.

Aruba 2930F 24G 4SFP+ Switch (JL253A)		
I/O ports and slots	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 7.88(d) x 1.73(h) in (44.25 x 20.02 x 4.39 cm) (1U height)
	Weight	5.31 lb (2.41 kg)
Memory and processor	Dual Core ARM Coretex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 1.6 μ s (64-byte packets)
	Throughput	up to 95.2 Mpps
	Switching capacity	128 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 49.7 dB, Pressure: 37.1 dB
	Airflow direction	Side-to-side
Electrical characteristics	Maximum heat dissipation	100 BTU/hr (105.5 kJ/hr)

	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	0.6/0.4 A
	Maximum power rating	29.3 W
	Idle power	19.5 W
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected.. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated..
Safety	UL 60950-1, 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	
<hr/>		
Aruba 2930F 48G 4SFP+ Switch (JL254A)		
I/O ports and slots	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 9.7(d) x 1.73(h) in (44.25 x 24.63 x 4.39 cm) (1U height)
	Weight	6.83 lb (3.10 kg)
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	

Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 1.6 μ s (64-byte packets)
	Throughput	up to 112.0 Mpps
	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 54.1 dB, Pressure: 40.2 dB
	Airflow direction	Side-to-side
Electrical characteristics	Maximum heat dissipation	157.2 BTU/hr (165.8 KJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	0.9/0.6 A
	Maximum power rating	46.6 W
	Idle power	32.7 W
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated..
Safety	UL 60950-1, 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8

	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	
<hr/>		
Aruba 2930F 24G PoE+ 4SFP+ Switch (JL255A)		
I/O ports and slots	24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	8.6 lb (3.9 kg)
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5 MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 1.6 μ s (64-byte packets)
	Throughput	up to 95.2 Mpps
	Switching capacity	128 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 54.1 dB, Pressure: 40.2 dB
	Airflow direction	Side-to-side
Electrical characteristics	80plus.org Certification	Silver
	Maximum heat dissipation	258.0 BTU/hr (272.2 KJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	4.9/2.4 A
	Maximum power rating	445 W
	Idle power	36.8 W

	PoE power	370 W PoE+
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated..
Safety	UL 60950-1 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	

Aruba 2930F 48G PoE+ 4SFP+ Switch ([JL256A](#))

I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	9.83 lb (4.46 kg)
Memory and processor	Dual Core ARM Coretex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 1.6 μ s (64-byte packets)
	Throughput	up to 112.0 Mpps

	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 55.7 dB, Pressure: 41.7 dB
	Airflow direction	Side-to-side
Electrical characteristics	80plus.org Certification	Silver
	Maximum heat dissipation	293.0 BTU/hr (309.1 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	5.1/2.5 A
	Maximum power rating	459 W
	Idle power	48.6 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz
Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
Safety	UL 60950-1 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and	IEC 61000-4-11

	interruptions	
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	
Aruba 2930F 8G PoE+ 2SFP+ Switch (JL258A)		
I/O ports and slots	8 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	2 SFP+ 1/10GbE ports; PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	10(w) x 10(d) x 1.73(h) in (25.4 x 25.4 x 4.39 cm) (1U height)
	Weight	4.41 lb (2.0 kg)
Memory and processor	Dual Core ARM Coretex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10 Gbps Latency	< 1.6 μ s (64-byte packets)
	Throughput	up to 41.7 Mpps
	Switching capacity	56 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 0 dB, Pressure: 0 dB Fanless
Electrical characteristics	Description	Power supply meets DoE VI certification.
	Maximum heat dissipation	58.6 BTU/hr (61.8 kJ/hr)
	Voltage	90 - 264 VAC, rated
	Current	2.6 A
	Maximum power rating	155 W
	PoE power	125 W PoE+
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-

		<p>case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).</p>
Safety	UL 60950-1 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	
<hr/>		
Aruba 2930F 24G 4SFP Switch (JL259A)		
I/O ports and slots	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 7.88(d) x 1.73(h) in (44.25 x 20.02 x 4.39 cm) (1U height)
	Weight	5.31 lb (2.41 kg)
Memory and processor	Dual Core ARM Coretex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 41.7 Mpps
	Switching capacity	56 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries

Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 49.7 dB, Pressure: 37.1 dB
	Airflow direction	Side-to-side
Electrical characteristics	Maximum heat dissipation	100 BTU/hr (105.5 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	0.6/0.4 A
	Maximum power rating	29.3 W
	Idle power	19.5 W
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band	

	management (serial RS-232C or micro USB)	
Aruba 2930F 48G 4SFP Switch (JL260A)		
I/O ports and slots	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 9.7(d) x 1.73(h) in (44.25 x 24.63 x 4.39 cm) (1U height)
	Weight	6.83 lb (3.10 kg)
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 77.4 Mpps
	Switching capacity	104 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C), noncondensing
	Acoustic	Power: 54.1 dB, Pressure: 40.2 dB
	Airflow direction	Side-to-side
Electrical characteristics	Maximum heat dissipation	100.0 BTU/hr (105.5 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	0.9/0.6 A
	Maximum power rating	46.6 W
	Idle power	32.7 W
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1, 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014	

	Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2:
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	

Aruba 2930F 24G PoE+ 4SFP Switch ([JL261A](#))

I/O ports and slots	24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	8.6 lb (3.9 kg)
Memory and processor	Dual Core ARM Coretex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 41.7 Mpps
	Switching capacity	56 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet

	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic	Power: 54.1 dB, Pressure: 40.6 dB
	Airflow direction	Side-to-side
Electrical characteristics	80plus.org Certification	Silver
	Maximum heat dissipation	258.0 BTU/hr (272.2 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	4.9/2.4 A
	Maximum power rating	445 W
	Idle power	36.8 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2:
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	
Aruba 2930F 48G PoE+ 4SFP Switch (JL262A)		

I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	4 SFP	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	9.83 lb (4.46 kg)
Memory and processor	Dual Core ARM Cortex @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.875MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 77.4 Mpps
	Switching capacity	104 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, - 0C to 40C (32F to 104F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic	Power: 55.7 dB, Pressure: 41.7 dB
	Airflow direction	Side-to-side
Electrical characteristics	80plus.org Certification	Silver
	Maximum heat dissipation	293.0 BTU/hr (309.1 kJ/hr)
	Voltage	100 - 127 / 200 - 240 VAC, rated
	Current	5.1/2.5 A
	Maximum power rating	459 W
	Idle power	48.6 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz
Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
Safety	UL 60950-1 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	

Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	

Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch (JL263A)

I/O ports and slots	24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASETX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in. (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	8.6 lb (3.9 kg)
Memory and processor	Dual Core ARM® Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB; 4.5 MB Ingress/7.785 MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μs (64-byte packets)
	10 Gbps Latency	< 1.6 μs (64-byte packets)
	Throughput	Up to 95.2 Mpps
	Switching capacity	128 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, -0°C to 40°C (32°F to 104°F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing

	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic	Power: 54.1 dB, Pressure: 40.6 dB
	Airflow direction	Side-to-side
Electrical characteristics	80plus.org Certification	Silver
	Maximum heat dissipation	258.0 BTU/hr (272.2kJ/hr)
	Voltage	100-127 / 200-240 VAC, rated
	Current	4.9/2.4 A
	Maximum power rating	445 W
	Idle power	36.8 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
	Safety	UL 69050-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line	

	interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	
Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch (JL264A)		
I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASETX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42(w) x 11.98(d) x 1.73(h) in. (44.25 x 30.42 x 4.39 cm) (1U height)
	Weight	9.83 lb (4.46 kg)
Memory and processor	Dual Core ARM® Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB; 4.5 MB Ingress/7.785 MB Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μs (64-byte packets)
	10 Gbps Latency	< 1.6 μs (64-byte packets)
	Throughput	Up to 112.0 Mpps
	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5000 Feet, -0°C to 40°C (32°F to 104°F) up to 10000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic	Power: 55.7 dB, Pressure: 41.7 dB
	Airflow direction	Side-to-side
Electrical characteristics	80plus.org Certification	Silver
	Maximum heat dissipation	293.0 BTU/hr (309.1 kJ/hr)
	Voltage	100-127 / 200-240 VAC, rated
	Current	5.1/2.5 A
	Maximum power rating	459 W
	Idle power	48.6 W
	PoE power	370 W PoE+
	Frequency	50/60 Hz

	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 69050-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	

Aruba 2930F 48G PoE+ 4SFP 740W Switch ([JL557A](#))

I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42 (w) x 12.77 (d) x 1.73 (h) in (44.25 x 32.42 x 4.39 cm) (1U height)
	Weight	10.56 lb (4.79 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	Throughput	up to 77.4 Mpps

	Switching capacity	104 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5,000 Feet, 0°C to 40°C (32°F to 104°F) up to 10,000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15,000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic (power and pressure) in decibals	Power: 55.1 dB, Pressure: 41.1 dB
	Airflow direction	Side to side
	Electrical characteristics	80plus.org Certification
Maximum heat dissipation		420.9 BTU/hr (444.1 kJ/hr)
Voltage		100-127 / 200-240 VAC, rated
Current		9.2 / 4.9 A
Maximum power rating		980W
Idle power		49.9W
PoE power		740 W PoE+
Frequency		50/60 Hz
Notes		Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 69050-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950- 1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825- 1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5

	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	

Aruba 2930F 48G PoE+ 4SFP+ 740W Switch ([JL558A](#))

I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42 (w) x 12.77 (d) x 1.73 (h) in (44.25 x 32.42 x 4.39 cm) (1U height)
	Weight	10.56 lb (4.79 kg)
Memory and processor	Dual Core ARM Cortex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress, 4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10Gbps latency	< 1.6 μ s (64-byte packets)
	Throughput	up to 112.0 Mpps
	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5,000 Feet, 0°C to 40°C (32°F to 104°F) up to 10,000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15,000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C)

	Acoustic (power and pressure) in decibals	Power: 55.1 dB, Pressure: 41.1 dB
	Airflow direction	Side to side
Electrical characteristics	80plus.org Certification	Gold
	Maximum heat dissipation	420.9 BTU/hr (444.1 kJ/hr)
	Voltage	100-127 / 200-240 VAC, rated
	Current	9.2 / 4.9 A
	Maximum power rating	980W
	Idle power	49.9W
	PoE power	740 W PoE+
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950-1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825-1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	
Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch (JL559A)		
I/O ports and slots	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type	

	100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ 1/10GbE ports PHY-less	
Additional ports and slots	1 dual-personality (RJ-45 or USB micro-B) serial console port	
Physical characteristics	Dimensions	17.42 (w) x 12.77 (d) x 1.73 (h) in (44.25 x 32.42 x 4.39 cm) (1U height)
	Weight	10.56 lb (4.79 kg)
Memory and processor	Dual Core ARM Coretex A9 @ 1016 MHz, 1 GB DDR3 SDRAM; Packet buffer size: 12.38 MB 4.5MB Ingress/7.785 Egress,4 GB eMMC	
Performance	1000 Mb Latency	< 3.8 μ s (64-byte packets)
	10Gbps latency	< 1.6 μ s (64-byte packets)
	Throughput	up to 112.0 Mpps
	Switching capacity	176 Gbps
	Routing table size	2,000 IPv4, 1,000 IPv6 in hardware, 200 OSPF, 256 Static, 10,000 RIP
	MAC address table size	32,768
Environment	Operating temperature	32°F to 113°F (0°C to 45°C); up to 5,000 Feet, 0°C to 40°C (32°F to 104°F) up to 10,000 Feet
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C); up to 15,000 Feet
	Nonoperating/Storage temperature	15% to 95% @ 149°F (65°C)
	Acoustic (power and pressure) in decibals	Power: 55.1 dB, Pressure: 41.1 dB
	Airflow direction	Side to side
Electrical characteristics	80plus.org Certification	Gold
	Maximum heat dissipation	420.9 BTU/hr (444.1 kJ/hr)
	Voltage	100-127 / 200-240 VAC, rated
	Current	9.2 / 4.9 A
	Maximum power rating	980W
	Idle power	49.9W
	PoE power	740 W PoE+
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected.

		Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 69050-1: 2nd Edition; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013; IEC 60950- 1:2005 +A1:2009 +A2:2013; CSA 22.2 No. 60950-1-07 2nd; EN 60825- 1:2014 / IEC 60825-1:2014 Class 1	
Emissions	EN 55032:2012/CISPR 32 Class A; FCC CFR 47 Part 15 Class A; VCCI Class A; ICES-003 Class A; CNS 13438	
Immunity	Generic	EN 55024:2010/CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	IEC/EN 61000-3-2
	Flicker	IEC/EN 61000-3-3
Management	Aruba AirWave Network Management; IMC – Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)	

Standards and protocols (applies to all products in series)

Denial of service protection	CPU DoS Protection
Device Management	<p>RFC 1155 Structure and Mgmt Information (SMIv1)</p> <p>RFC 1157 SNMPv1/v2c</p> <p>RFC 1591 DNS (client)</p> <p>RFC 1901 (Community based SNMPv2)</p> <p>RFC 1901-1907 SNMPv2c, SMIv2 and Revised MIB-II</p> <p>RFC 1908 (SNMP v1/2 Coexistence)</p> <p>RFC 2576 (Coexistence between SNMP V1, V2, V3)</p> <p>RFC 2578-2580 SMIv2</p> <p>RFC 2579 (SMIv2 Text Conventions)</p> <p>RFC 2580 (SMIv2 Conformance)</p> <p>RFC 2819 (RMON groups Alarm, Event, History and Statistics only)</p> <p>RFC 3416 (SNMP Protocol Operations v2)</p> <p>RFC 3417 (SNMP Transport Mappings)</p>

	<p>HTML and telnet management</p> <p>HTTP, SSHv1, and Telnet</p> <p>Multiple Configuration Files</p> <p>Multiple Software Images</p> <p>SNMP v3 and RMON RFC support</p> <p>SSHv1/SSHv2 Secure Shell</p> <p>TACACS/TACACS+</p> <p>Web UI</p>
General Protocols	<p>IEEE 802.1AX-2008 Link Aggregation</p> <p>IEEE 802.1D MAC Bridges</p> <p>IEEE 802.1p Priority</p> <p>IEEE 802.1Q VLANs</p> <p>IEEE 802.1s Multiple Spanning Trees</p> <p>IEEE 802.1v VLAN classification by Protocol and Port</p> <p>IEEE 802.1w Rapid Reconfiguration of Spanning Tree</p> <p>IEEE 802.3ab 1000BASE-T</p> <p>IEEE 802.3ad Link Aggregation Control Protocol (LACP)</p> <p>IEEE 802.3af Power over Ethernet</p> <p>IEEE 802.3at PoE+</p> <p>IEEE 802.3az Energy Efficient Ethernet</p> <p>IEEE 802.3x Flow Control</p> <p>RFC 768 UDP</p> <p>RFC 783 TFTP Protocol (revision 2)</p> <p>RFC 792 ICMP</p> <p>RFC 793 TCP</p> <p>RFC 826 ARP</p> <p>RFC 854 TELNET</p> <p>RFC 868 Time Protocol</p> <p>RFC 951 BOOTP</p> <p>RFC 1058 RIPv1</p> <p>RFC 1256 ICMP Router Discovery Protocol (IRDP)</p> <p>RFC 1350 TFTP Protocol (revision 2)</p> <p>RFC 1519 CIDR</p> <p>RFC 1542 BOOTP Extensions</p> <p>RFC 1918 Address Allocation for Private Internet</p> <p>RFC 2030 Simple Network Time Protocol (SNTP) v4</p> <p>RFC 2131 DHCP</p> <p>RFC 2236 IGMP Snooping</p> <p>RFC 2453 RIPv2</p> <p>RFC 2865 Remote Authentication Dial In User Service (RADIUS)</p> <p>RFC 2866 RADIUS Accounting</p> <p>RFC 3046 DHCP Relay Agent Information Option</p>

	<p>RFC 3411 An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks</p> <p>RFC 3412 Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)</p> <p>RFC 3413 Simple Network Management Protocol (SNMP) Applications</p> <p>RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)</p> <p>RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)</p> <p>RFC 3416 Protocol Operations for SNMP</p> <p>RFC 3417 Transport Mappings for the Simple Network Management Protocol (SNMP)</p> <p>RFC 3418 Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)</p> <p>RFC 3575 IANA Considerations for RADIUS</p> <p>RFC 3576 Ext to RADIUS (CoA only)</p> <p>RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches</p> <p>RFC 4675 RADIUS VLAN & Priority</p> <p>RFC 4861 Neighbor Discovery for IP version 6 (IPv6)</p> <p>RFC 4862 IPv6 Stateless Address Autoconfiguration</p> <p>RFC 5905 Network Time Protocol Version 4: Protocol and Algorithms Specification</p> <p>UDLD (Uni-directional Link Detection)</p>
IP Multicast	<p>RFC 1112 IGMP</p> <p>RFC 2236 IGMPv2</p> <p>RFC 2710 Multicast Listener Discovery (MLD) for IPv6</p> <p>RFC 3376 IGMPv3</p> <p>RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches</p>
IPv6	<p>RFC 1981 IPv6 Path MTU Discovery</p> <p>RFC 2080 RIPng for IPv6</p> <p>RFC 2081 RIPng Protocol Applicability Statement</p> <p>RFC 2082 RIP-2 MD5</p> <p>RFC 2460 IPv6 Specification</p> <p>RFC 2464 Transmission of IPv6 over Ethernet Networks</p> <p>RFC 2710 Multicast Listener Discovery (MLD) for IPv6</p> <p>RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)</p> <p>RFC 2925 Remote Operations MIB (Ping only)</p> <p>RFC 3019 MLDv1 MIB</p> <p>RFC 3315 DHCPv6 (client and relay)</p> <p>RFC 3484 Default Address Selection for IPv6</p> <p>RFC 3513 IPv6 Addressing Architecture</p>

	<p>RFC 3596 DNS Extension for IPv6</p> <p>RFC 3810 MLDv2 for IPv6</p> <p>RFC 4022 MIB for TCP</p> <p>RFC 4113 MIB for UDP</p> <p>RFC 4251 SSHv6 Architecture</p> <p>RFC 4252 SSHv6 Authentication</p> <p>RFC 4253 SSHv6 Transport Layer</p> <p>RFC 4254 SSHv6 Connection</p> <p>RFC 4291 IP Version 6 Addressing Architecture</p> <p>RFC 4293 MIB for IP</p> <p>RFC 4419 Key Exchange for SSH</p> <p>RFC 4443 ICMPv6</p> <p>RFC 4541 IGMP & MLD Snooping Switch</p> <p>RFC 4861 IPv6 Neighbor Discovery</p> <p>RFC 4862 IPv6 Stateless Address Auto-configuration</p> <p>RFC 5095 Deprecation of Type 0 Routing Headers in IPv6</p> <p>RFC 6620 FCFS SAVI</p> <p>draft-ietf-savi-mix</p>
MIBs	<p>IEEE 802.1ap (MSTP and STP MIB's only)</p> <p>IEEE 8021-Bridge-MIB (2008)</p> <p>IEEE 8021-Q-Bridge-MIB (2008)</p> <p>RFC 1155 Structure & ID of Mgmt Info for TCP/IP Internets</p> <p>RFC 1156 (TCP/IP MIB)</p> <p>RFC 1157 A Simple Network Management Protocol (SNMP)</p> <p>RFC 1213 MIB II</p> <p>RFC 1493 Bridge MIB</p> <p>RFC 1724 RIPv2 MIB</p> <p>RFC 2021 RMONv2 MIB</p> <p>RFC 2578 Structure of Management Information Version 2 (SMIv2)</p> <p>RFC 2579 Textual Conventions for SMIv2</p> <p>RFC 2580 Conformance Statements for SMIv2</p> <p>RFC 2613 SMON MIB</p> <p>RFC 2618 RADIUS Client MIB</p> <p>RFC 2620 RADIUS Accounting MIB</p> <p>RFC 2665 Ethernet-Like-MIB</p> <p>RFC 2668 802.3 MAU MIB</p> <p>RFC 2674 802.1p and IEEE 802.1Q Bridge MIB</p> <p>RFC 2737 Entity MIB (Version 2)</p> <p>RFC 2819 RMON MIB</p> <p>RFC 2863 The Interfaces Group MIB</p> <p>RFC 2925 Ping MIB</p> <p>RFC 2932 IP (Multicast Routing MIB)</p>

	<p>RFC 2933 IGMP MIB</p> <p>RFC 3414 SNMP-User based-SM MIB</p> <p>RFC 3415 SNMP-View based-ACM MIB</p> <p>RFC 3417 Simple Network Management Protocol (SNMP) over IEEE 802 Networks</p> <p>RFC 3418 MIB for SNMPv3</p> <p>RFC 4836 Managed Objects for 802.3 Medium Attachment Units (MAU)</p>
Network Management	<p>IEEE 802.1AB Link Layer Discovery Protocol (LLDP)</p> <p>RFC 1155 Structure of Management Information</p> <p>RFC 1157 SNMPv1</p> <p>RFC 2021 Remote Network Monitoring Management Information Base Version 2 using SMIv2</p> <p>RFC 2576 Coexistence between SNMP versions</p> <p>RFC 2578 Structure of Management Information Version 2 (SMIv2)</p> <p>RFC 2579 Textual Conventions for SMIv2</p> <p>RFC 2580 Conformance Statements for SMIv2</p> <p>RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)</p> <p>RFC 2819 Remote Network Monitoring Management Information Base</p> <p>RFC 2856 Textual Conventions for Additional High Capacity Data Types</p> <p>RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations</p> <p>RFC 3164 BSD syslog Protocol</p> <p>RFC 3176 sFlow</p> <p>RFC 3411 SNMP Management Frameworks</p> <p>RFC 3412 Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)</p> <p>RFC 3413 Simple Network Management Protocol (SNMP) Applications</p> <p>RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)</p> <p>RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)</p> <p>RFC 3418 Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)</p> <p>RFC 5424 Syslog Protocol</p> <p>ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)</p> <p>SNMPv1/v2c/v3</p> <p>XRMON</p>
QoS/CoS	<p>IEEE 802.1p (CoS)</p> <p>RFC 2474 DiffServ Precedence, including 8 queues/port</p> <p>RFC 2475 DiffServ Architecture</p> <p>RFC 2597 DiffServ Assured Forwarding (AF)</p> <p>RFC 2598 DiffServ Expedited Forwarding (EF)</p> <p>Ingress Rate Limiting</p>
Security	<p>IEEE 802.1X Port Based Network Access Control</p> <p>RFC 1321 The MD5 Message-Digest Algorithm</p>

RFC 1334 PPP Authentication Protocols (PAP)
RFC 1492 An Access Control Protocol, Sometimes Called TACACS
RFC 1492 TACACS+
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message Authentication
RFC 2138 RADIUS Authentication
RFC 2139 RADIUS Accounting
RFC 2246 Transport Layer Security (TLS)
RFC 2548 Microsoft Vendor-specific RADIUS Attributes
RFC 2618 RADIUS Authentication Client MIB
RFC 2620 RADIUS Accounting Client MIB
RFC 2698 A Two Rate Three Color Marker
RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2818 HTTP Over TLS
RFC 2865 RADIUS (client only)
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 2867 RADIUS Accounting Modifications for Tunnel Protocol Support
RFC 2868 RADIUS Attributes for Tunnel Protocol Support
RFC 2869 RADIUS Extensions
RFC 2882 NAS Requirements: Extended RADIUS Practices
RFC 3162 RADIUS and IPv6
RFC 3576 Dynamic Authorization Extensions to RADIUS
RFC 3579 RADIUS Support For Extensible Authentication Protocol (EAP)
RFC 3580 IEEE 802.1X RADIUS
RFC 3580 IEEE 802.1X Remote Authentication Dial In User Service (RADIUS) Usage Guidelines
RFC 4675 RADIUS Attributes
Access Control Lists (ACLs)
draft-grant-tacacs-02 (TACACS)
Guest VLAN for 802.1X
MAC Authentication
MAC Lockdown
MAC Lockout
Port Security
Secure Sockets Layer (SSL)
SSHv2 Secure Shell
Web Authentication

The table shows the Aruba 2930F Switch Series accessories.

Transceivers	
Aruba 100M SFP LC FX 2km MMF Transceiver	J9054D
Aruba 1G SFP RJ45 T 100m Cat5e Transceiver	J8177D
Aruba 1G SFP LC SX 500m OM2 MMF Transceiver	J4858D
Aruba 1G SFP LC LX 10km SMF Transceiver	J4859D
Aruba 1G SFP LC LH 70km SMF Transceiver	J4860D
Aruba 10G SFP+ LC SR 300m OM3 MMF Transceiver	J9150D
Aruba 10G SFP+ LC LR 10km SMF Transceiver	J9151D
Aruba 10G SFP+ LC ER 40km SMF Transceiver	J9153D
Aruba 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	J9281D
Aruba 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283D
NOTE: no support for J9152D 10G LRM, nor J9285D 10G 7m DAC	
Cables	
Aruba X2C2 RJ45 to DB9 Console Cable	JL448A
HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A
Aruba 2930F 24G 4SFP+ Switch (JL253A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 48G 4SFP+ Switch (JL254A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 24G PoE+ 4SFP+ Switch (JL255A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 48G PoE+ 4SFP+ Switch (JL256A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 8G PoE+ 2SFP+ Switch (JL258A)	
Aruba 2930F 8-port Cable Guard	JL311A
Aruba 2930F 8-port Power Shelf	JL312A

Aruba 2930F 24G 4SFP Switch (JL259A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 48G 4SFP Switch (JL260A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 24G PoE+ 4SFP Switch (JL261A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 48G PoE+ 4SFP Switch (JL262A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 24G PoE+ 4SFP+ TAA-compliant Switch (JL263A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 48G PoE+ 4SFP+ TAA-compliant Switch (JL264A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 48G PoE+ 4SFP 740W Switch (JL557A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 48G PoE+ 4SFP+ 740W Switch (JL558A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A
Aruba 2930F 48G PoE+ 4SFP+ 740W TAA-compliant Switch (JL559A)	
HPE X410 1U Universal 4-post Rackmount Kit	J9583A

ORDERING INFORMATION

Order the Aruba 2930F switches here:

Models	Description
JL253A	Aruba 2930F 24G 4SFP+ Switch, Delivery period: 1-2 weeks
JL254A	Aruba 2930F 48G 4SFP+ Switch, Delivery period: 1-2 weeks
JL255A	Aruba 2930F 24G PoE+ 4SFP+ Switch, Delivery period: 1-2 weeks
JL256A	Aruba 2930F 48G PoE+ 4SFP+ Switch, Delivery period: 1-2 weeks
JL258A	Aruba 2930F 8G PoE+ 2SFP+ Switch, Delivery period: 1-2 weeks
JL259A	Aruba 2930F 24G 4SFP Switch, Delivery period: 1-2 weeks
JL260A	Aruba 2930F 48G 4SFP Switch, Delivery period: 1-2 weeks
JL261A	Aruba 2930F 24G PoE+ 4SFP Switch, Delivery period: 1-2 weeks
JL262A	Aruba 2930F 48G PoE+ 4SFP Switch, Delivery period: 1-2 weeks
JL558A	Aruba 2930F 48G PoE+ 4SFP+ 740W Switch, Delivery period: 1-2 weeks
JL557A	Aruba 2930F 48G PoE+ 4SFP 740W Switch, Delivery period: 1-2 weeks

Want to buy this series of products? please contact:

- Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com (Sales Inquiries)

Or visit: [Aruba 2930F Series Switches](#)

About us

Router-switch.com (HongKong Yejian Technologies Co., Ltd), founded in 2002, is one of the biggest Global Network Hardware Supplier. We are a leading provider of network products with 14,500+ customers in over 200 countries. We provide original new and used network equipments (Cisco, Huawei, HPE, Dell, Juniper, EMC, etc.), including Routers, Switches, Servers, Storage, Telepresence and Videoconferencing, IP Phones, Firewalls, Wireless APs & Controllers, EHWIC/HWIC/VWIC Cards, SFPs, Memory & Flash, Hard Disk, Cables, and all kinds of network solutions related products. Our technical team provides Free CCIE technical support and brings effective solutions to customers. We carry over \$20 million of network products in RSHub™ to meet the needs of SOHO, small, midsize and large businesses of all sizes; develop RSCare™ to serve customers better; introduce the RSLab™ to provide more technical supports and customized network solutions for you. We build the big data team and digital marketing to help clients find the best network products and set up the smartest networks.

SOURCES

<https://h20195.www2.hp.com/v2/gethtml.aspx?docname=c05052929>