

Overview

HPE Ethernet 10/25Gb 2-port 622FLR-SFP28 Converged Network Adapter

Extended SKU - This adapter is part of an extended catalog of products tailored for customers in specific markets or with specific workloads, requiring the utmost in performance or value, but typically have a longer lead-time.

The HPE Ethernet 10/25Gb 2-port 622FLR-SFP28 Converged Network Adapter for ProLiant servers are designed to optimize Cloud efficiency, and improve performance and security of applications - especially where I/O, block storage and database performance are critical and the need for maximum VM density and up-scalability are greatest.

The HPE Ethernet 10/25Gb 2-port 622FLR-SFP28 Converged Network Adapter can provide up to 100Gbps of converged bi-directional Ethernet bandwidth, helping to alleviate network bottlenecks. This adapter can also run at 10 Gb for customers who have not changed the infrastructure/switches to 25 Gb yet.



Overview



HPE Ethernet 10/25Gb 2-port 622FLR-SFP28 Converged Network Adapter

Platform Information

Models

HPE Ethernet 10/25Gb 2-port 622FLR-SFP28 Converged Network Adapter

867334-B21

Kit Contents

HPE Ethernet 10/25Gb 2-port 622FLR-SFP28 Converged Network Adapter
Quick install card
Product warranty statement

Compatibility - Supported Servers

HPE ProLiant DL120 Gen10 Server
HPE ProLiant DL160 Gen10 Server
HPE ProLiant DL180 Gen10 Server
HPE ProLiant DL360 Gen10 Server
HPE ProLiant DL380 Gen10 Server
HPE ProLiant DL385 Gen10 Server
HPE ProLiant DL560 Gen10 Server
HPE ProLiant DL580 Gen10 Server
HPE Apollo 2000 - XL170r Gen10 Server
HPE Apollo 2000 - XL190r Gen10 Server
HPE Apollo 4500 - XL450 Gen10 Server

NOTE: This is a list of supported servers. Some may be discontinued.

Standard Features

At a Glance Features

- Dual 25 Gb ports provide up to 100 Gb/s of converged bi-directional Ethernet bandwidth
- Jumbo Frame
- FlexibleLOM
- HPE Sea of Sensors 3D
- Tunnel Offload(NVGRE and VxLAN)
- RDMA over Converged Ethernet (RoCE v2, RoCE v1)
- Single-root input/output virtualization (SR-IOV)
- IPv6 Acceleration
- Preboot eXecution Environment (PXE)
- Checksum & Segmentation Offload
- VMware NetQueue and Microsoft Virtual Machine Queue (VMQ)
- Precision Time Protocol (PTP)
- Support for Wake on LAN (WoL)
- Receive-Side Scaling (RSS)
- Receive-Side Coalescing (RSC)
- Data Plane Development Kit (DPDK)
- Active Health Systems support
- Authentication of digitally signed firmware
- Additional Security features include: UEFI Secure Boot, Sanitization, Audit Logs and Device-level Firewall
- Full RDMA –enable the iWARP stacks on adapters in addition to the ROCE capability. (No iWarp and RoCE on the same port)

NOTE: DPDK not supported with HPE Virtual Connect SE 40Gb F8 Module.

Storage personality must be disabled on NIC intended for DPDK workload. DPDK and Storage modes cannot be used concurrently on current generation CNA NICs. HPE Recommends using 2 separate NICS for Storage (Control Plane), and DPDK (Data Plane) workloads for the optimal high availability configuration. No DPDK with storage mode. No DPDK with VC interconnects.

Throughput-Theoretical Bandwidth	This adapter delivers 50 Gb/s bi-directional Ethernet transfer rate per port (100 Gb/s per adapter), providing the network performance needed to improve response times and alleviate bottlenecks.
Audit Logs	Audit Logs are a forensics capability that provides traceability into authenticated firmware updates by capturing changes in standard system logs.
Authenticated Updates	Authenticated Updates brings cryptographic keys onto the NIC (for HW Authentication) to protect user and configuration data from unauthorized access and verify digitally signed firmware.
Checksum & Segmentation Offload	Normally the TCP Checksum is computed by the protocol stack. Segmentation Offload is technique for increasing outbound throughput of high-bandwidth network connections by reducing CPU overhead. The

Standard Features

technique is also called TCP segmentation offload (TSO) when applied to TCP, or generic segmentation offload (GSO).

Device-level Firewall	Device-level Firewall blocks any unmanaged access to memory or storage. This ensures that on-device firmware and configuration data can only be accessed by authorized agents.
------------------------------	--

Form Factor	This adapter series offers FlexibleLOM.
--------------------	---

HPE Sea Of Sensors 3D	Support for the HPE Sea of Sensors which is a collection of 32 sensors that automatically track thermal activity - heat - across the server. When temperatures get too high, sensors can initiate fans and make other adjustments to reduce energy usage. A significant improvement lies in the ability to apply fan speed increases only to the portion of the system that is rising in temperature, rather than all six fans in unison, which reduces the amount of energy used for cooling.
------------------------------	--

IPv6	IPv6 uses 128-bit addressing allowing for more devices and users on the internet. IPv4 supported 32-bit addressing.
-------------	---

Jumbo Frames	This adapter supports Jumbo Frames (also known as extended frames), permitting up to a 9,600 byte (KB) transmission unit (MTU) when running Ethernet I/O traffic. This is over six times the size of a standard 1500-byte Ethernet frame. With Jumbo Frames, networks can achieve higher throughput performance and greater CPU utilization. These attributes are particularly useful for database transfer and tape backup operations.
---------------------	---

Management Support	This adapter ships with agents that can be managed from HPE Systems Insight Manager or other management application that support SNMP.
---------------------------	--

Preboot eXecution Environment (PXE)	Support for PXE enables automatic deployment of computing resources remotely from anywhere. It allows a new or existing server to boot over the network and download software, including the operating system, from a management/ deployment server at another location on the network. Additionally, PXE enables decentralized software distribution and remote troubleshooting and repairs.
--	---

RoCE v2	This adapter supports RoCE v1 and v2. RoCE v2, also sometimes called "Routable RoCE" which adds Concurrent RoCE v1 and v2 support, SR-IOV support, QoS with hierarchical TX scheduling, ECN-based congestion control for RoCE v2. RoCE is an accelerated I/O delivery mechanism that allows data to be transferred directly from the user memory of the source server to the user memory of the destination server bypassing the operating system (OS) kernel. Because the RDMA data transfer is performed by the DMA engine on the adapter's network processor, the CPU is not used for the data movement, freeing it to perform other tasks such as hosting more virtual workloads (increased VM density). RDMA also bypasses the host's TCP/IP stack, in favor of upper layer InfiniBand protocols implemented in the adapter's network processor. The bypass of the TCP/IP stack and the removal of a data copy step reduce overall latency to deliver accelerated performance for applications such as Microsoft Hyper-V Live Migration, Microsoft SQL and Microsoft SharePoint with SMB Direct.
----------------	---

Standard Features

Receive Side Scaling (RSS)	RSS resolves the single-processor bottleneck by allowing the receive side network load from a network adapter to be shared across multiple processors. RSS enables packet receive-processing to scale with the number of available processors.
Sanitization	Sanitization (Secure User Data Erase) renders User and configuration data on the NIC irretrievable so that NICs can be safely repurposed or disposed.
Secure Boot	Secure Boot safeguards the system and ensures no rogue drivers are being executed on start-up.
Server Integration	<p>This adapter is a validated, tested, and qualified solution that is optimized for HPE ProLiant servers. Hewlett Packard Enterprise validates a wide variety of major operating systems drivers with the full suite of web-based enterprise management utilities including HPE Intelligent Provisioning and HPE Systems Insight Manager that simplify network management.</p> <p>This approach provides a more robust and reliable networking solution than offerings from other vendors and provides users with a single point of contact for both their servers and their network adapters.</p>
Single-Root I/O Virtualization	Single-Root I/O Virtualization (SR-IOV) provides a mechanism to bypass the host system hypervisor in virtual environments providing near metal performance and server efficiency. SR-IOV provides mechanism to create multiple Virtual Functions (VFs) to share single PCIe resources. The device is capable of SR-IOV, and requires Server BIOS support, controller firmware, and OS support.
Precision Time Protocol (IEEE 1588 PTP)	Synchronization of system clocks throughout a network, achieving clock accuracy in the sub-microsecond range, making it suitable for measurement and control systems.
Tunnel Offload	Minimize the impact of overlay networking on host performance with tunnel offload support for VXLAN and NVGRE. By offloading packet processing to adapters, customers can use overlay networking to increase VM migration flexibility and virtualized overlay networks with minimal impact to performance. HPE Tunnel Offloading increases I/O throughput, reduces CPU utilization, and lowers power consumption. Tunnel Offload supports VMware's VXLAN and Microsoft's NVGRE solutions.
VMware NewQueue and Microsoft Virtual Machine Queue (VMQ)	<p>VMware NetQueue is technology that significantly improves performance of 10 Gigabit Ethernet network adapters in virtualized environments.</p> <p>Windows Hyper-V VMQ (VMQ) is a feature available on servers running Windows Server 2008 R2 with VMQ-enabled Ethernet adapters. VMQ uses hardware packet filtering to deliver packet data from an external virtual machine network directly to virtual machines, which reduces the overhead of routing packets and copying them from the management operating system to the virtual machine.</p>

Standard Features

Wake-on-LAN

This adapter provides Wake-on-LAN (WoL) support through the PCI Express bus. A system that supports Wake-on-LAN can remain available to the systems administrator during its normal downtime. Once the machine is awakened, the systems administrator can remotely control, audit, debug, or manage the machine.

Warranty

Maximum: The remaining warranty of the HPE product in which it is installed (to a maximum three-year, limited warranty).

Minimum: One year limited warranty.

NOTE: Additional information regarding worldwide limited warranty and technical support is available at: <http://h17007.www1.hp.com/us/en/enterprise/servers/warranty/index.aspx#.V4e3tPkrJhE>

Service and Support

Service and Support **NOTE: This adapter is covered under HPE Support Services/ Service Contract applied to the HPE ProLiant Server or enclosure. No separate HPE Support Services# need to be purchased.**

Most HPE branded options sourced from HPE that are compatible with your product will be covered under your main product support at the same level of coverage, allowing you to upgrade freely. Additional support is required on select workload accelerators, switches, racks and UPS options 12KVA and over. Coverage of the UPS battery is not included under HPE support services; standard warranty terms and conditions apply.

Warranty and Support Services

Warranty and Support Services will extend to include HPE options configured with your server or storage device. The price of support service is not impacted by configuration details. HPE sourced options that are compatible with your product will be covered under your server support at the same level of coverage allowing you to upgrade freely. Installation for HPE options is available as needed. To keep support costs low for everyone, some high value options will require additional support. Additional support is only required on select high value workload accelerators, fibre switches, InfiniBand and UPS options 12KVA and over. Coverage of the UPS battery is not included under TS support services; standard warranty terms and conditions apply.

Protect your business beyond warranty with HPE Support Services

HPE Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to HPE to help prevent problems and solve issues faster. HPE Support Services enable you to choose the right service level, length of coverage and response time as you purchase your new server, giving you full entitlement to the support you need for your IT and business. Protect your product, beyond warranty.

Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements. Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services. The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.

For more information

Visit the Hewlett Packard Enterprise Service and Support [website](#).

Related Options

Cables - Direct Attach	HPE 25 GbE SFP28 to SFP28 0.5m Direct Attach Copper Cable	844471-B21	
	HPE 25 GbE SFP28 to SFP28 1m Direct Attach Copper Cable	844474-B21	
	HPE 25 GbE SFP28 to SFP28 3m Direct Attach Copper Cable	844477-B21	
	HPE 25 GbE SFP28 to SFP28 5m Direct Attach Copper Cable	844480-B21	
	HPE 100G QSFP28 to 4x25G SFP28 3m Direct Attach Copper Splitter Cable	845416-B21	
	HPE 100G QSFP28 to 4x25G SFP28 5m Direct Attach Copper Splitter Cable	845418-B21	
	HP Blc 10G SFP+ 0.5m DAC Cable	487649-B21	
	HP Blc 10G SFP+ 1m DAC Cable	487652-B21	
	HP Blc 10G SFP+ 3m DAC Cable	487655-B21	
	HP Blc 10G SFP+ 7m DAC Cable	487658-B21	
	HP Blc 10G SFP+ 5m DAC Cable	537963-B21	
	HP X240 10G SFP+ SFP+ 0.65m DAC Cable	JD095C	
	HP X240 10G SFP+ SFP+ 1.2m DAC Cable	JD096C	
	HP X240 10G SFP+ SFP+ 3m DAC Cable	JD097C	
	HP X240 10G SFP+ SFP+ 5m DAC Cable	JG081C	
	HP X240 10G SFP+ SFP+ 7m DAC Cable	JC784C	
	HP X242 10G SFP+ to SFP+ 1m Direct Attach Copper Cable	J9281B	
	HP X242 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	J9283B	
	HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable	J9285B	
	HP .5m Multi-mode OM3 LC/LC FC Cable	AJ833A	
	HP 1m Multi-mode OM3 LC/LC FC Cable	AJ834A	
	HP 5m Multi-mode OM3 LC/LC FC Cable	AJ836A	
	HP 15m Multi-mode OM3 LC/LC FC Cable	AJ837A	
	HP 30m Multi-mode OM3 LC/LC FC Cable	AJ838A	
	HP 50m Multi-mode OM3 LC/LC FC Cable	AJ839A	
	Transceivers	HPE 25Gb SFP28 SR Transceiver (100m)	845398-B21
		HP Blc 10G SFP+ SR Transceiver	455883-B21
HP X132 10G SFP+ LC SR Transceiver		J9150A	
HP Blc 10G SFP+ LR Transceiver		455886-B21	

Technical Specifications

General Specifications	Network Processor	Cavium QL41402
	Data Rate	Two ports, each at 50 Gbps bi-directional; 100 Gbps bi-directional theoretical bandwidth.
	Bus type	PCIe 3.0 x8
	Form Factor	FlexibleLOM
	IEEE Compliance	802.3by, 802.1Qau, 802.1Qaz, 802.1Qbb, 802.1Qbg, 802.3az 802.1AS, 802.3ad, IEEE1588
	Connector	Two SFP28 (SR, LR, DAC)

Power and Environmental Specifications	Power	12.5 W typical, 15 W maximum
	Temperature - Operating	5° to 60° C (41° to 140° F)
	Temperature - Non-Operating	-40°C to 70°C / -40°F to 158°F
	Humidity - Operating	System relative humidity: Minimum to be the higher (more moisture) of -12°C (10.4°F) dew point or 8% relative humidity. Maximum to be the lower (less moisture) of 24°C (75.2°F) dew point or 90% relative humidity. non-condensing.
	Humidity - Non-operating	5 to 95% relative humidity, non-condensing.
	Other	PCIe 3.0 RoHS compliance 6 of 6 IPv4, IPv6 CE Microsoft WHQL (Windows Hardware Quality Labs)

Operating System and Virtualization Support	The Operating Systems supported by this adapter are based on the server OS support. Please refer to the OS Support Matrix at https://www.hpe.com/us/en/servers/server-operating-systems.html .
--	--

Environment-friendly Products and Approach - End-of-life Management and Recycling	Hewlett Packard Enterprise offers end-of-life product return, trade-in, and recycling programs in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner. The EU WEEE Directive (2012/19/EU) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard Enterprise web site . These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.
--	--

Summary of Changes

Date	Version History	Action	Description of Change
05-Mar-2018	Version 4	Updated	Models and Compatibility-Supported Servers section was updated
05-Feb-2018	Version 3	Updated	Overview was Updated
16-Oct-2017	Version 2	Updated	Overview and Standard Features- At a Glance Features were updated.
25-Sep-2017	Version 1	Created	New QuickSpecs.



Sign up for updates



© Copyright 2018 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

a00021589enw - 16046 - Worldwide - V4 -05-March-2018