



Huawei

AP5030DN AP5130DN

Access Points

Datasheet



Product Overview

The AP5030DN and AP5130DN are Huawei's latest-generation 802.11ac Wave 1 access points.

They support 3 x 3 MIMO and provide industry-leading capabilities in terms of high-density access, multi-user performance, signal coverage, and anti-interference. The two APs work on both 2.4 GHz and 5 GHz frequency bands and are backward compatible with 802.11a/b/g/n standards.

The 802.11ac-capable APs make a major leap in Wi-Fi access from 100M to GE and meet the bandwidth requirements of large-bandwidth services such as High Definition (HD) video streams, multimedia, and desktop cloud services, delivering smooth and high-quality wireless services to enterprise users.



AP5030DN



AP5130DN

- 802.11ac Wave 1 standards compliance, delivering services simultaneously on 2.4G and 5G radios; 450 Mbit/s at 2.4 GHz; 1.3 Gbit/s at 5 GHz; and 1.75 Gbit/s for the device.
- PoE power supply in compliance with IEEE 802.3af/at for easy installation.
- Dual GE interfaces support interface backup to ensure reliability. Fat AP and Fit AP working modes.
- AP5130DN: uses external antennas. Antennas can be configured and deployment locations determined according to network requirements. External antennas are delivered with APs in the standard configuration, and provide 2.5 dBi gain at 2.4 GHz and 4 dBi gain at 5 GHz.
- AP5030DN: uses built-in antennas with 4 dBi gain at 2.4 GHz and 5 dBi gain at 5 GHz.

Feature Description

802.11ac GE access

The APs support the 80-MHz bandwidth mode. Frequency bandwidth increase brings extended channels and more sub-carriers for data transmission, and a 2.16 times higher rate.

High Quadrature Amplitude Modulation (HQAM) at 256-QAM increases the 5 GHz radio rate to 1.3 Gbit/s. The throughput of 802.11ac APs is twice that of traditional APs.

High Density Boost technology

Huawei uses the following technologies to address challenges in high-density scenarios, including access problems, data congestion, and poor roaming experience:

- Interference suppression

- In high-density scenarios, APs are usually densely placed. Huawei uses small-angle antennas that are purpose-built for high-density scenarios to mitigate interference. These antennas have good radiation angle control and can regulate AP coverage radius to within the appropriate range. Additionally, Huawei's Clear Channel Assessment (CCA) optimization technology reduces the possibility of air port resources shared by multiple devices, allows higher user access, and improves the throughput.

- Air port performance optimization

- In high-density scenarios where many users access the network, the increased number of low-rate STAs consumes more resources on the air port, reduces the AP capacity, and lowers user experience. Therefore, Huawei APs will check the signal strength of STAs during access and reject access from weak-signal STAs. At the same time, the APs monitor the rate of online STAs in real time and forcibly disconnect low-rate STAs so that the STAs can reassociate with APs that have stronger signals. Terminal access control technology can increase air port use efficiency and allow access from more users.

- 5G-prior access

- The APs support both 2.4G and 5G frequency bands. The 5G-prior access function enables an AP to steer STAs to the 5 GHz frequency band first, which reduces load and interference on the 2.4 GHz frequency band, improving user experience.

- Load balancing between APs

- After the load balancing function is enabled, the AC distributes users evenly to APs based on user quantity and traffic volume. Traffic load is therefore balanced among APs to ensure stable AP performance.

- Smart roaming

- Smart roaming technology is based on the 802.11k and 802.11v technologies and allows STAs to connect to APs with stronger signals, improving user experience and the overall performance of the wireless network.
- These measures together help construct a wireless expressway network that can accommodate more terminals.

Wired and wireless dual security guarantee

To ensure data security, Huawei APs integrate wired and wireless security measures and provide comprehensive security protection.

- Authentication and encryption for wireless access

- The APs support WEP, WPA/WPA2-PSK, WPA/WPA2-802.1x, and WAPI authentication/encryption modes to ensure security of the wireless network. The authentication mechanism is used to authenticate user identities so that only authorized users can access network resources. The encryption mechanism is used to encrypt data transmitted over wireless links to ensure that the data can only be received and parsed by expected users.

- Analysis on non-Wi-Fi interference sources

- Huawei APs can analyze the spectrum of non-Wi-Fi interference sources and identify them, including baby monitors, Bluetooth devices, digital cordless phones (at 2.4 GHz frequency band only), wireless audio transmitters (at both the 2.4 GHz and 5 GHz frequency bands), wireless game controllers, and microwave ovens. Coupled with Huawei eSight, the precise locations of the interference sources can be detected, and the spectrum of them displayed, enabling the administrator to remove the interference in a timely manner.

- Rogue device monitoring

- Huawei APs support WIDS/WIPS, and can monitor, identify, defend, counter, and perform refined management on the rogue devices, to provide security guarantees for air interface environment and wireless data transmission.

- **AP access authentication and encryption**
 - The AP access control ensures validity of APs. The CAPWAP link protection and DTLS encryption provide security assurance, improving data transmission security between the AP and the AC.

Automatic radio calibration

Automatic radio calibration allows an AP to collect signal strength and channel parameters of surrounding APs and generate AP topology according to the collected data. Based on interference from authorized APs, rogue APs, and non-Wi-Fi interference sources, each AP automatically adjusts its transmit power and working channel to make the network operate at the optimal performance. In this way, network reliability and user experience are improved.

Automatic application identification

Huawei APs support smart application control technology and can implement visualized control on Layer 4 to Layer 7 applications.

- **Traffic identification**
 - Coupled with Huawei ACs, the APs can identify over 800 common applications in various office scenarios. Based on the identification results, policy control can be implemented on user services, including priority adjustment, scheduling, blocking, and rate limiting to ensure efficient bandwidth resource use and improve quality of key services.
- **Traffic statistics collection**
 - Traffic statistics of each application can be collected globally, by SSID, or by user, enabling the network administrator to know application use status on the network. The network administrator or operator can implement visualized control on service applications on smart terminals to enhance security and ensure effective bandwidth control.

Basic Specifications..... //

Hardware specifications

| Item | | Description |
|--------------------------|---------------------------|--|
| Technical specifications | Dimensions (H x W x D) | 53 mm x 220 mm x 220 mm |
| | Weight | 1.0 kg |
| | Interface type | 2 x 10/100/1000M self-adaptive Ethernet interface (RJ45) 1 x Management console port (RJ45) |
| | LED indicator | Indicates the power-on, startup, running, alarm, and fault status of the system. |
| Power specifications | Power input | <ul style="list-style-type: none">• 12 V DC \pm 10%• PoE power supply: -48 V DC (in compliance with IEEE 802.3af/at) |
| | Maximum power consumption | 12.95W NOTE The actual maximum power consumption depends on local laws and regulations. |

| Item | | Description |
|------------------------------|---------------------------------------|---|
| Environmental specifications | Operating temperature | −10°C to +50°C |
| | Storage temperature | −40°C to +70°C |
| | Operating humidity | 5% to 95% (non-condensing) |
| | Dustproof and waterproof grade | IP41 |
| | Altitude | −60 m to +5000 m |
| | Atmospheric pressure | 70 kPa to 106 kPa |
| Radio Specifications | Antenna type | AP5030DN: built-in antennas (horizontal beamwidth 360°) AP5130DN: external dual-band antennas |
| | Antenna gain | <ul style="list-style-type: none">AP5030DN: 4 dBi (2.4 GHz); 5 dBi (5 GHz)AP5130DN: 3.5 dBi (2.4 GHz); 4 dBi (5 GHz) |
| | Maximum number of VAPs for each radio | 16 |
| | Maximum number of users | ≤ 256 |
| | Maximum transmit power | 2.4G: 25dBm(combined power); 5G: 25dBm(combined power) NOTE The actual transmit power depends on local laws and regulations. |
| | Power increment | 1 dBm |
| | Receiver sensitivity | 2.4 GHz 802.11b (CCK): −96 dBm @ 1 Mb/s; −89 dBm @ 11 Mb/s |
| | | 2.4 GHz 802.11g (non-HT20): −87 dBm @ 6 Mb/s; −74 dBm @ 54 Mb/s |
| | | 2.4 GHz 802.11n (HT20): −87 dBm @ MCS0; −71 dBm @ MCS7 |
| | | 2.4 GHz 802.11n (HT40): −84 dBm @ MCS0; −68 dBm @ MCS7 |
| | | 5 GHz 802.11a (non-HT20): −90 dBm @ 6 Mb/s; −73 dBm @ 54 Mb/s |
| | | 5 GHz 802.11n (HT20): −89 dBm @ MCS0; −70 dBm @ MCS7 |
| | | 5 GHz 802.11n (HT40): −86 dBm @ MCS0; −66 dBm @ MCS7 |
| | | 5 GHz 802.11ac (VTH20): −88 dBm @ MCS0NSS1; −65 dBm @ MCS8NSS1 |
| | | 5 GHz 802.11ac (VTH40): −85 dBm @ MCS0NSS1; −60 dBm @ MCS9NSS1 |
| | | 5 GHz 802.11ac (VTH80): −82 dBm @ MCS0NSS1; −57 dBm @ MCS9NSS1 |

Software Specifications


| Item | Description |
|---------------|--|
| WLAN features | <ul style="list-style-type: none">• Compliance with IEEE 802.11a/b/g/n/ac• Maximum rate: 1.75 Gbit/s• Maximum Ratio Combining (MRC)• Cyclic Delay Diversity (CDD)/Cyclic Shift Diversity (CSD)• Maximum Likelihood Detection (MLD)• Data unit aggregation, including A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx)• 802.11 Dynamic Frequency Selection (DFS)• Short Guard Interval (GI) in 20 MHz, 40 MHz, and 80 MHz modes• Priority mapping and packet scheduling based on a Wi-Fi Multimedia (WMM) profile to implement priority-based data processing and forwarding• Automatic and manual rate adjustment (the rate is adjusted automatically by default)• WLAN channel management and channel rate adjustment• Automatic channel scanning and interference avoidance• Service Set Identifier (SSID) hiding, support for SSIDs in Chinese• Signal Sustain Technology (SST)• Unscheduled Automatic Power Save Delivery (U-APSD)• Control and Provisioning of Wireless Access Points (CAPWAP) in Fit AP mode• Automatic access in Fit AP mode• WDS in Fit AP mode• Mesh networking in Fit AP mode• Dual-MPP Mesh networking in Fit AP mode• Hotspot2.0 in Fit AP mode• 802.11k and 802.11v smart roaming in Fit AP mode• Fast roaming (≤ 50 ms) |

| Item | Description |
|-------------------|---|
| Network features | <ul style="list-style-type: none">• Compliance with IEEE 802.3u• Auto-negotiation of the rate and duplex mode; automatic switchover between the Media Dependent Interface (MDI) and Media Dependent Interface Crossover (MDI-X)• SSID-based VLAN assignment• VLAN trunk on uplink Ethernet ports• 4094 VLAN IDs (1 to 4094) and a maximum of 16 virtual APs (VAPs) for each radio• AP control channel in tagged and untagged mixed mode• DHCP client, obtaining IP addresses through DHCP• Tunnel forwarding and direct forwarding• STA isolation in the same VLAN• Multicast Domain Name Service (mDNS) gateway protocol: supports AirPlay and AirPrint service sharing between users of different VLANs• Access control lists (ACLs)• Link Layer Discovery Protocol (LLDP)• Service holding upon CAPWAP link disconnection in Fit AP mode• Unified authentication on the AC in Fit AP mode• AC dual-link backup in Fit AP mode• Soft Generic Routing Encapsulation (GRE)• IPv6 Portal• IPv6 Source Address Validation Improvements (SAVI)• IPv4/IPv6 ACLNetwork Address Translation (NAT) |
| QoS features | <ul style="list-style-type: none">• Priority mapping and packet scheduling based on a WMM profile to implement priority-based data processing and forwarding• WMM parameter management for each radio• WMM power saving• Priority mapping for upstream packets and flow-based mapping for downstream packets• Queue mapping and scheduling• User-based bandwidth limiting• Adaptive bandwidth management (the system dynamically adjusts bandwidth based on the number of users and radio environment to improve user experience)• Airtime fair scheduling• Support for Microsoft Lync APIs and high voice call quality through Lync API identification and scheduling |
| Security features | <ul style="list-style-type: none">• Open system authentication• WEP authentication/encryption• WPA/WPA2-PSK authentication and encryption• WPA/WPA2-802.1x authentication and encryption• WPA-WPA2 authentication• WAPI authentication and encryption• WIDS including rogue AP and STA detection, attack detection, STA/AP blacklist and whitelist• 802.1x authentication, MAC address authentication, and Portal authentication• 802.11w Protected Management Frames (PMFs) |


| Item | Description |
|----------------------|---|
| Maintenance features | <ul style="list-style-type: none">• Unified management and maintenance on the AC in Fit AP mode• Plug-and-Play (PnP) in Fit AP mode: automatic ally going online and loading configurations• WDS zero-configuration deployment in Fit AP mode• WMN zero-configuration deployment in Fit AP mode• Batch upgrade• Local AP management through the serial port or using Telnet• Real-time configuration monitoring and fast fault location using the NMS• System status alarm• STelnet using Secure Shell (SSH) v2• Secure File Transfer Protocol (SFTP) using SSH v2• Web local AP management through HTTP or HTTPS in Fat AP mode• Simple Network Management Protocol (SNMP) v1/v2/v3 in Fat AP mode• Network Time Protocol (NTP) in Fat AP mode |
| BYOD | <ul style="list-style-type: none">• Identifies the device type according to the Organizationally Unique Identifier (OUI) in the MAC address.• Identifies the device type according to the User Agent (UA) information in an HTTP packet• Identifies the device type according to DHCP options.• The RADIUS server delivers packet forwarding, security, and QoS policies according to the device type carried in the RADIUS authentication and accounting packets. |
| Locating service | <ul style="list-style-type: none">• Locates tags manufactured by AeroScout or Ekahau.• Locates Wi-Fi terminals. |
| Spectrum analysis | <ul style="list-style-type: none">• Identifies interference sources such as baby monitors, Bluetooth devices, digital cordless phones (at 2.4 GHz frequency band only), wireless audio transmitters (at both the 2.4 GHz and 5 GHz frequency bands), wireless game controllers, and microwave ovens.• Works with Huawei eSight to locate and perform spectrum analysis on interference sources. |

Standards Compliance


| Item | Description | | |
|-------------------------|---|---|--|
| Safety standards | UL 60950-1 CAN/CSA 22.2 No.60950-1 | IEC 60950-1 EN 60950-1 | GB 4943 |
| Radio standards | ETSI EN 300 328 ETSI EN 301 893 FCC Part 15C: 15.247 | FCC Part 15C: 15.407 RSS-210 | AS/NZS 4268 FCC Part 15.107 and 15.109 |
| EMC standards | EN 301 489-1 EN 301 489-17 ETSI EN 60601-1-2 FCC Part 15 ICES-003 YD/T 1312.2-2004 | ITU k.21 GB 9254 GB 17625.1 AS/NZS CIPSR22 EN 55022 | EN 55024 CISPR 22 CISPR 24 IEC61000-4-6 IEC61000-4-2 |
| IEEE standards | IEEE 802.11a/b/g IEEE 802.11n IEEE 802.11ac IEEE 802.11h | IEEE 802.11u IEEE 802.11v IEEE 802.11w | IEEE 802.11d IEEE 802.11e IEEE 802.11k |
| Security standards | 802.11i, Wi-Fi Protected Access 2 (WPA2), WPA 802.1x Advanced Encryption Standards (AES), Temporal Key Integrity Protocol (TKIP), and Extensible Authentication Protocol (EAP) types: <ul style="list-style-type: none">EAP-Transport Layer Security (TLS)EAP-Tunneled TLS (TTLS) or Microsoft Challenge Handshake Authentication Protocol Version 2 (MSCHAPv2)Protected EAP (PEAP) v0 or EAP-MSCHAPv2EAP-Flexible Authentication via Secure Tunneling (FAST)PEAP v1 or EAP-Generic Token Card (GTC) EAP-Subscriber Identity Module (SIM) | | |
| Environmental standards | ETSI 300 019-2-1 ETSI 300 019-2-2 | ETSI 300 019-2-3 ETSI 300 019-1-1 | ETSI 300 019-1-2 ETSI 300 019-1-3 |
| EMF | CENELEC EN 62311 CENELEC EN 50385 | OET65 RSS-102 | FCC Part1&2 FCC KDB series |
| RoHS | Directive 2002/95/EC & 2011/65/EU | | |
| Reach | Regulation 1907/2006/EC | | |
| WEEE | Directive 2002/96/EC & 2012/19/EU | | |
| Certifications | Wi-Fi Alliance (WFA) certified 802.11a/b/g/n/ac | | |

AP5030DN Antenna Pattern Plots


2.4G (PHI=0)



2.4G (PHI=90)



5G (PHI=0)



5G (PHI=90)

Ordering Information

| Component | Part Description | Configuration Description | Remarks |
|-----------------------------|--|---|--|
| AP | | | |
| AP5030DN | Assembling Components,AP5030DN,AP5030DN Mainframe(11ac,General AP Indoor,3x3 Double Frequency,Built-in Antenna,No AC/DC adapter) | The mounting bracket is included in the standard configuration. | The standard configuration does not include the network cable. |
| AP5130DN | Assembling Components,AP5130DN,AP5130DN Mainframe(11ac,General AP Indoor,3x3 Double Frequency,External Antenna,No AC/DC adapter) | The mounting bracket is included in the standard configuration. | The standard configuration does not include the network cable. |
| Power Adapter | | | |
| 220 V to 12 V power adapter | AC/DC Adapter--5degC-45degC-90V-270V-12V/2A-Europe Standard-DC inlet | European standard | Sold only on markets outside China. |
| 220 V to 12 V power adapter | AC/DC Adapter--5degC-45degC-90V-270V-12V/2A-UK Standard-DC inlet | UK standard | Sold only on markets outside China. |
| 220 V to 12 V power adapter | AC/DC Adapter--5degC-45degC-90V-270V-12V/2A-Australia Standard-DC inlet | Australian standard | Sold only on markets outside China. |
| 220 V to 12 V power adapter | Adapter--5degC-45degC-90V-270V-12V/2A-Brazil Standard-DC inlet | Brazilian standard | Sold only on markets outside China. |
| 220 V to 12 V power adapter | Adapter,-5degC,45degC,90V,270V,12V/2A,US Standard/DC inlet | US standard | Sold only on markets outside China. |

Professional Service and Support

Huawei WLAN planning tools deliver expert network design and optimization services using the most professional simulation platform in the industry. Backed by fifteen years of continuous investment in wireless technologies, extensive network planning and optimization experience, and rich expert resources, Huawei helps customers:

- Design, deploy, and operate a high-performance network that is reliable and secure.
- Maximize return on investment and reduce operating expenses.

More Information

For more information, please visit <http://e.huawei.com/en/> or contact your local Huawei office.



Enterprise Services



Product Overview




Marketing Documentation

Copyright © Huawei Technologies Co., Ltd. 2016. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademark Notice



HUAWEI, and  are trademarks or registered trademarks of Huawei Technologies Co., Ltd. Other trademarks, product, service and company names mentioned are the property of their respective owners.

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO.,LTD.
Huawei Industrial Base
Bantian Longgang
Shenzhen 518129,P.R.China
Tel: +86 755 28780808

www.huawei.com