



# Huawei S5730-SI Series

## Switches Datasheet



**Router-Switch.com**  
Leading Network Hardware Supplier

## CONTENT

Overview .....	2
Models & Appearance .....	2
Key Features and Benefits .....	3
Product Specifications .....	6
Basic Ordering Information.....	13
Where to Buy .....	15
Sources.....	15

### Contact Us

Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166

Fax: +852-3050-1066 (Hong Kong)

Email: [sales@router-switch.com](mailto:sales@router-switch.com) (Sales Inquiries)

## OVERVIEW

Huawei's S5730-SI series switches (S5730-SI for short) are next-generation standard gigabit Layer 3 Ethernet switches that provide flexible full gigabit access and cost-effective fixed GE ports and 10 GE uplink ports, meanwhile can provide 40 GE uplink ports with an interface card. The S5730-SI was developed based on next-generation high-performing hardware and the Huawei Versatile Routing Platform (VRP). The S5730-SI supports simplified Operations and Maintenance (O&M), intelligent Stack (iStack), flexible Ethernet networking. It also provides enhanced Layer 3 features and mature IPv6 features. The S5730-SI can be used in various scenarios. For example, it can be used as an access or aggregation switch on a campus network or as an access switch in a data center.

## MODELS & APPEARANCE

### 1. S5730-48C-SI-AC



- 24 Ethernet 10/100/1,000 ports, 8 x 10 Gig SFP+
- One interface slot
- Dual pluggable AC or DC power supplies, one 150W AC power supply equipped by default
- Forwarding performance: 240 Mpps; Switching capacity: 680 Gbit/s

### 2. S5730-48C-PWR-SI-AC



- 24 Ethernet 10/100/1,000 ports, 8 x 10 Gig SFP+
- One interface slot
- One 500W AC power supply equipped by default
- PoE+
- Forwarding performance: 240 Mpps; Switching capacity: 680 Gbit/s

### 3. S5730-68C-SI-AC



- 48 Ethernet 10/100/1,000 ports, 4 x 10 Gig SFP+
- One interface slot
- Dual pluggable AC or DC power supplies, one 150W AC power supply equipped by default
- Forwarding performance: 240 Mpps; Switching capacity: 680 Gbit/s

#### 4. S5730-68C-PWR-SI-AC



- 48 Ethernet 10/100/1,000 ports, 4 x 10 Gig SFP+,
- One interface slot
- One 500W AC power supply equipped by default
- PoE+
- Forwarding performance: 240 Mpps; Switching capacity: 680 Gbit/s

#### 5. S5730-68C-PWR-SI



- 48 Ethernet 10/100/1,000 ports, 4 x 10 Gig SFP+, PoE+
- One interface slot
- PoE+
- Forwarding performance: 240 Mpps; Switching capacity: 680 Gbit/s

## KEY FEATURES AND BENEFITS

### Powerful service processing capability and multiple security control mechanisms

The S5730-SI supports many Layer 2/Layer 3 multicast protocols such as PIM SM, PIM DM, PIM SSM, MLD, and IGMP snooping, to support multi-terminal high-definition video surveillance and video conferencing services.

The S5730-SI supports multiple Layer 3 features including OSPF, IS-IS, BGP, and VRRP, meeting enterprises' requirements for access and aggregation service transmission, and enabling a variety of voice, video, and data applications.

The S5730-SI supports MAC address authentication, 802.1x authentication, and Portal authentication, and implements dynamic delivery of policies (VLAN, QoS, and ACL) to users.

The S5730-SI provides a series of mechanisms to defend against DoS and user-targeted attacks. DoS attacks are targeted at switches and include SYN flood, Land, Smurf, and ICMP flood attacks. User-targeted attacks include bogus DHCP server attacks, IP/MAC address spoofing, DHCP request flood, and change of the DHCP CHADDR value.

The S5730-SI sets up and maintains a DHCP snooping binding table, and discards the packets that do not match the table entries. You can specify DHCP snooping trusted and untrusted ports to ensure that users connect only to the authorized DHCP server.

The S5730-SI supports strict ARP learning, which protects a network against ARP spoofing attacks to ensure normal network access.

### **Easy O&M**

The S5730-SI supports Super Virtual Fabric (SVF), which virtualizes the “Core/aggregation + Access switch + AP” structure into a logical device. The S5730-SI provides the simplest network management solution in the industry to simplify device management. It allows plug-and-play access switches and APs. In addition, the S5730-SI supports service configuration templates. The templates are configured on core devices and automatically delivered to access devices, enabling centralized control, simplified service configuration, and flexible configuration modification. The S5730-SI functions as a client in an SVF system.

The S5730-SI supports zero-touch deployment, replacement of faulty devices without additional configuration, USB-based deployment, batch configuration, and batch remote upgrade. The capabilities facilitate device deployment, upgrade, service provisioning, and other management and maintenance operations, and also greatly reduce O&M costs. The S5730-SI can be managed using SNMP v1/v2c/v3, CLI, web-based network management system, or SSH v2.0. Additionally, it supports RMON, multiple log hosts, port traffic statistics collection, and network quality analysis, which facilitate network optimization and reconstruction.

The S5730-SI supports the Sampled Flow (sFlow) function. It uses a method defined in the sFlow standard to sample traffic passing through it and sends sampled traffic to the collector in real time. The collected traffic statistics are used to generate statistical reports, helping enterprises maintain their networks.

### **Multiple reliability mechanisms**

The S5730-SI supports iStack. This technology can virtualize up to nine physical switches into one logical switch. Downlink electrical ports support iStack. Member switches in a stack implement redundancy backup to improve device reliability and use inter-device link aggregation to improve link reliability. iStack provides high network scalability. You can increase a stack’s ports, bandwidth, and processing capacity by simply adding member switches. iStack also simplifies device configuration and management. After a stack is set up, multiple physical switches are virtualized into one logical device. You can log in to any member switch in the stack to manage all the member switches in the stack.

The S5730-SI is equipped with two removable power modules that can work in 1+1 redundancy backup mode. Mixed installation of AC and DC power modules is supported, allowing for flexible configuration of AC or DC power modules according to service requirements.

In addition to traditional STP, RSTP, and MSTP, the S5730-SI supports Huawei-developed Smart Ethernet Protection (SEP) technology and the latest Ethernet Ring Protection Switching (ERPS) standard. SEP is a ring protection protocol specific to the Ethernet link layer, and applies to various ring network topologies, such as open ring topology, closed ring topology, and cascading ring topology. This protocol is reliable, easy to maintain, and implements fast protection switching within 50 ms. ERPS is defined in ITU-T G.8032. It implements millisecond-level protection switching based on traditional Ethernet MAC and bridging functions.

The S5730-SI supports Smart Link. One S5730-SI switch can connect to multiple aggregation switches through multiple links, implementing backup of uplinks and significantly improving reliability of access devices.

The S5730-SI supports Ethernet OAM (IEEE 802.3ah/802.1ag) to detect link faults quickly.

### **Mature IPv6 technologies**

The S5730-SI uses the mature, stable VRRP platform and supports IPv4/IPv6 dual stack, IPv6 RIPng, and IPv6 over IPv4 tunnels (including manual, 6-to-4, and ISATAP tunnels). With these IPv6 features, the S5730-SI can be deployed on a pure IPv4 network, a pure IPv6 network, or a shared IPv4/IPv6 network, helping achieve IPv4-to-IPv6 transition.

### **OPS**

Open Programmability System (OPS) is an open programmable system based on the Python language. IT administrators can program the O&M functions of a switch through Python scripts to quickly innovate functions and implement intelligent O&M.

### **PoE**

Perpetual PoE: When a PoE switch is rebooted after the software version is upgraded, the power supply to PDs is not interrupted. This capability ensures that PDs are not powered off during the switch reboot.

Fast PoE: S5730-48C/68C-PWR-SI switches can supply power to PDs within 10s after they are powered on. This is different from common switches that generally take 1 to 3 minutes to start to supply power to PDs. When a PoE switch reboots due to a power failure, the PoE switch continues to supply power to the PDs immediately after being powered on without waiting until it finishes reboot. This greatly shortens the power failure time of PDs.

### **Intelligent O&M**

The S5730-SI provides telemetry technology to collect device data in real time and send the data to Huawei campus network analyzer CampusInsight. The CampusInsight analyzes network data based on the intelligent fault identification algorithm, accurately displays the real-time network status, effectively demarcates and locates faults in a timely manner, and identifies network problems that affect user experience, accurately guaranteeing user experience.

The S5730-SI supports a variety of intelligent O&M features for audio and video services, including the enhanced Media Delivery Index (eMDI). With this eMDI function, the switch can function as a monitored node to periodically conduct statistics and report audio and video service indicators to the CampusInsight platform. In this way, the CampusInsight platform can quickly demarcate audio and video service quality faults based on the results of multiple monitored nodes.

## PRODUCT SPECIFICATIONS

Item	<u>S5730-48C-SI-AC</u>	<u>S5730-48C-PWR-SI-AC</u>	<u>S5730-68C-SI-AC</u>	<u>S5730-68C-PWR-SI-AC</u>	<u>S5730-68C-PWR-SI</u>
<b>Fixed Ports</b>	24 x 10/100/1,000 Base-T, 8 x 10 Gig SFP+	24 x 10/100/1,000 Base-T, 8 x 10 Gig SFP+	48 x 10/100/1,000 Base-T, 4 x 10 Gig SFP+	48 x 10/100/1,000 Base-T, 4 x 10 Gig SFP+	48 x 10/100/1,000 Base-T, 4 x 10 Gig SFP+
<b>MAC Address Table</b>	32K MAC				
<b>Dimensions (W x D x H)</b>	442 mm x 420 mm x 44.4 mm	442 mm x 420 mm x 44.4 mm	442 mm x 420 mm x 44.4 mm	442 mm x 420 mm x 44.4 mm	442 mm x 420 mm x 44.4 mm
<b>Slot</b>	One extended slot that supports an interface card: 4 x 40 GE QSFP+ interface card	One extended slot that supports an interface card: 4 x 40 GE QSFP+ interface card	One extended slot that supports an interface card: 4 x 40 GE QSFP+ interface card	One extended slot that supports an interface card: 4 x 40 GE QSFP+ interface card	One extended slot that supports an interface card: 4 x 40 GE QSFP+ interface card
	AC:	AC:	AC:	AC:	AC:

Item	<u>S5730-48C-SI-AC</u>	<u>S5730-48C-PWR-SI-AC</u>	<u>S5730-68C-SI-AC</u>	<u>S5730-68C-PWR-SI-AC</u>	<u>S5730-68C-PWR-SI</u>
<b>Input Voltage</b>	Rated AC voltage: 100V to 240V; 50/60 Hz  Max AC voltage: 90V to 264V; 47 Hz to 63 Hz	Rated AC voltage: 100V to 240V; 50/60 Hz  Max AC voltage: 90V to 264V; 47 Hz to 63 Hz	Rated AC voltage: 100V to 240V; 50/60 Hz  Max AC voltage: 90V to 264V; 47 Hz to 63 Hz	Rated AC voltage: 100V to 240V; 50/60 Hz  Max AC voltage: 90V to 264V; 47 Hz to 63 Hz	Rated AC voltage: 100V to 240V; 50/60 Hz  Max AC voltage: 90V to 264V; 47 Hz to 63 Hz
	DC:  Rated DC power: -48V to -60V  Max DC voltage: -36V to -72V	DC:  Rated DC power: -48V to -60V  Max DC voltage: -36V to -72V	DC:  Rated DC power: -48V to -60V  Max DC voltage: -36V to -72V	DC:  Rated DC power: -48V to -60V  Max DC voltage: -36V to -72V	DC:  Rated DC power: -48V to -60V  Max DC voltage: -36V to -72V
<b>Maximum Power Consumption</b>	Without card: 62.4W	Without card and PD: 83.2W  Without card and full PoE load: 967W (PoE: 740W)	Without card: 65.4W	Without card and PD: 68.3W  Without card and full PoE load: 925W (switch power consumption: 185W, PoE: 740W) with AC 500W/DC 650W power supply	Without card and PD: 68.3W  Without card and full PoE load: 925W (switch power consumption: 185W, PoE: 740W) with AC 500W/DC 650W power supply  Without card and full PoE load:

Item	<u>S5730-48C-SI-AC</u>	<u>S5730-48C-PWR-SI-AC</u>	<u>S5730-68C-SI-AC</u>	<u>S5730-68C-PWR-SI-AC</u>	<u>S5730-68C-PWR-SI</u>
					1,733W (switch power consumption: 294W, PoE: 1,440W) with AC 1,150W power supply
<b>Typical Power Consumption (without PD)</b>	Without card: 39.02W	Without card: 44.2W	Without card: 42.3W	Without card: 50.1W	Without card: 50.1W
<b>Operating Temperature</b>	0m to 1,800m altitude: 0°C to 45°C (long-term); -5°C to 50°C (short-term) 1,800m to 5,000m altitude: The operating temperature reduces by 1°C for each 220m increase in altitude.	0m to 1,800m altitude: 0°C to 45°C (long-term); -5°C to 50°C (short-term) 1,800m to 5,000m altitude: The operating temperature reduces by 1°C for each 220m increase in altitude.	0m to 1,800m altitude: 0°C to 45°C (long-term); -5°C to 50°C (short-term) 1,800m to 5,000m altitude: The operating temperature reduces by 1°C for each 220m increase in altitude.	0m to 1,800m altitude: 0°C to 45°C (long-term); -5°C to 50°C (short-term) 1,800m to 5,000m altitude: The operating temperature reduces by 1°C for each 220m increase in altitude.	0m to 1,800m altitude: 0°C to 45°C (long-term); -5°C to 50°C (short-term) 1,800m to 5,000m altitude: The operating temperature reduces by 1°C for each 220m increase in altitude.
<b>Relative Humidity</b>	5% to 95% (non-condensing)				

<b>Item</b>	<b><u>S5730-48C-SI-AC</u></b>	<b><u>S5730-48C-PWR-SI-AC</u></b>	<b><u>S5730-68C-SI-AC</u></b>	<b><u>S5730-68C-PWR-SI-AC</u></b>	<b><u>S5730-68C-PWR-SI</u></b>
<b>Heat Dissipation</b>	Heat dissipation using fans supporting intelligent speed adjustment	Heat dissipation using fans supporting intelligent speed adjustment	Heat dissipation using fans supporting intelligent speed adjustment	Heat dissipation using fans supporting intelligent speed adjustment	Heat dissipation using fans supporting intelligent speed adjustment
<b>Surge Protection</b>	Surge protection capability of service ports: 7 kV	Surge protection capability of service ports: 7 kV	Surge protection capability of service ports: 7 kV	Surge protection capability of service ports: 7 kV	Surge protection capability of service ports: 7 kV

<b>Service features</b>	
<b>MAC Address Table</b>	IEEE 802.1d compliance
	32K MAC address entries
	MAC address learning and aging
	Static, dynamic, and blackhole MAC address entries
	Packet filtering based on source MAC addresses
<b>VLAN</b>	4094 VLANs
	Guest VLAN and voice VLAN
	GVRP
	MUX VLAN

	VLAN assignment based on MAC addresses, protocols, IP subnets, policies, and ports
	1:1 and N:1 VLAN mapping
<b>Reliability</b>	RRPP ring topology and RRPP multi-instance
	Smart Link tree topology and Smart Link multi-instance, providing millisecond-level protection switchover
	SEP
	STP (IEEE 802.1d), RSTP (IEEE 802.1w), and MSTP (IEEE 802.1s)
	ERPS (G.8032)
	BPDU protection, root protection, and loop protection
<b>IP Routing</b>	Static route, RIPv1/v2, RIPv6, OSPF, OSPFv3, ECMP, IS-IS, IS-ISv6, BGP, BGP4+, VRRP, and VRRP6
<b>Multicast</b>	PIM DM, PIM SM, and PIM SSM
	IGMP v1/v2/v3 and IGMP v1/v2/v3 snooping and IGMP fast leave
	MLD v1/v2 and MLD v1/v2 snooping
	Multicast forwarding in a VLAN and multicast replication between VLANs
	Multicast load balancing among member ports of a trunk
	Controllable multicast
	Port-based multicast traffic statistics
<b>IPv6 Features</b>	Neighbor Discovery (ND)
	Path MTU (PMTU)

	IPv6 ping, IPv6 tracert, and IPv6 Telnet
	6to4 tunnel, ISATAP tunnel, and manually configured tunnel
	ACLs based on the source IPv6 address, destination IPv6 address, Layer 4 ports, or protocol type
<b>QoS/ACL</b>	Rate limiting on packets sent and received by a port
	Packet redirection
	Port-based traffic policing and two-rate three-color CAR
	Eight queues on each port
	WRR, DRR, SP, WRR + SP, and DRR + SP queue scheduling algorithms
	Re-marking of the 802.1p priority and DSCP priority
	Packet filtering at Layer 2 to Layer 4, filtering out invalid frames based on the source MAC address, destination MAC address, source IP address, destination IP address, TCP/UDP port number, protocol type, and VLAN ID
Rate limiting in each queue and traffic shaping on ports	
<b>Security</b>	Hierarchical user management and password protection
	DoS attack defense, ARP attack defense, and ICMP attack defense
	Binding of the IP address, MAC address, port number, and VLAN ID
	Port isolation, port security, and sticky MAC
	MFF
	Blackhole MAC address entries
	Limit on the number of learned MAC addresses

	IEEE 802.1x authentication and limit on the number of users on a port
	AAA authentication, RADIUS authentication, HWTACACS authentication, and NAC
	SSH v2.0
	HTTPS
	CPU defense
	Blacklist and whitelist
	IEEE 802.1x authentication, MAC address authentication, and Portal authentication
	DHCPv4/v6 client/relay/server/snooping
	Attack source tracing and punishment for IPv6 packets such as ND, DHCPv6, and MLD packets
<b>SVF</b>	Plug-and-play SVF client
	Automatic software and patch loading to clients
	One-click and automatic delivery of service configurations
	Independent client running
<b>OAM</b>	Software OAM
	EFM OAM
	CFM OAM
	Y.1731 performance test
	iStack (using service ports as stack ports)
	Virtual cable test

<b>Management and Maintenance</b>	SNMP v1/v2c/v3
	RMON
	Web-based NMS
	System logs and alarms of different levels
	802.3az EEE
	sFlow
	Intelligent O&M
<b>Interoperability</b>	Supports VBST (compatible with PVST/PVST+/RPVST)
	Supports LNP (similar to DTP)
	Supports VCMP (similar to VTP)

## BASIC ORDERING INFORMATION

<b>Model</b>	<b>Product Description</b>
<a href="#"><b><u>S5730-48C-SI-AC</u></b></a>	S5730-48C-SI Bundle (24 x Ethernet 10/100/1,000 ports, 8 x 10 Gig SFP+, with 1 interface slot, with 150W AC power supply)
<a href="#"><b><u>S5730-48C-PWR-SI-AC</u></b></a>	S5730-48C-PWR-SI Bundle (24 x Ethernet 10/100/1,000 ports, 8 x 10 Gig SFP+, PoE+, with 1 interface slot, with 500W AC power supply)
<a href="#"><b><u>S5730-68C-SI-AC</u></b></a>	S5730-68C-SI Bundle (48 x Ethernet 10/100/1,000 ports, 4 x 10 Gig SFP+, with 1 interface slot, with 150W AC power supply)
<a href="#"><b><u>S5730-68C-PWR-SI-AC</u></b></a>	S5730-68C-PWR-SI Bundle (48 x Ethernet 10/100/1,000 ports, 4 x 10 Gig SFP+, PoE+, with 1 interface slot, with 500W AC power supply)

<b><u>S5730-68C-PWR-SI</u></b>	S5730-68C-PWR-SI (48 x Ethernet 10/100/1,000 ports, 4 x 10 Gig SFP+, PoE+, with 1 interface slot, without power module)
<b><u>ES5D21Q04Q01</u></b>	4-port 40 GE QSFP+ interface card
<b><u>ES0W2PSA0150</u></b>	150W AC Power Module (Black)
<b><u>ES0W2PSD0150</u></b>	150W DC Power Module (Black)
<b><u>PAC-500WA-BE</u></b>	500W AC PoE Power Module (Black, power panel side exhaust)
<b><u>PDC-650WA-BE</u></b>	650W DC PoE Power Module (Black, power panel side exhaust)
<b><u>PAC1000D5412</u></b>	1,000W AC PoE Power Module
<b><u>W2PSA1150</u></b>	1,150W AC PoE Power Module
<b><u>SSD-240GB</u></b>	240 GB SSD card

## WHERE TO BUY

**Want to buy this series of products? please contact:**

- Tel: +1-626-239-8066 (USA)/ +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: [sales@router-switch.com](mailto:sales@router-switch.com) (Sales Inquiries)

**Or visit:** [Huawei S5730-SI Series Switches](#)

### About us

Router-switch.com, founded in 2002, is one of the biggest Global Network Hardware Supplier. We are a leading provider of network products with 14,500+ customers in over 200 countries. We provide original new and used network equipments (Cisco, Huawei, HPE, Dell, Juniper, EMC, etc.), including Routers, Switches, Servers, Storage, Telepresence and Videoconferencing, IP Phones, Firewalls, Wireless APs & Controllers, EHWIC/HWIC/VWIC Cards, SFPs, Memory & Flash, Hard Disk, Cables, and all kinds of network solutions related products.

## SOURCES

<https://e.huawei.com/us/related-page/products/enterprise-network/switches/campus-switches/s5700/brochure/switches-s5730-si>