



Juniper EX4300 Series Ethernet Switches Datasheet



Router-Switch.com
Leading Network Hardware Supplier

CONTENT

Content.....	1
Overview.....	2
Product Description.....	2
Appearance.....	4
Features and Benefits.....	5
Product Options.....	9
Specifications.....	12
Ordering information.....	26
Where to Buy.....	29
Sources.....	29

Contact Us

Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166 /

Fax: +852-3050-1066 (Hong Kong)

Email: sales@router-switch.com (Sales Inquiries)

OVERVIEW

The EX4300 line of Ethernet switches delivers the performance, flexibility, and scale required for both campus and data center Gigabit Ethernet (GbE) access switch environments. Whether deployed in a Virtual Chassis configuration or as a satellite device in a Juniper Networks Junos Fusion fabric architecture, the EX4300 delivers the operational simplicity and higher logical scale that businesses demand. Combining compact, pay-as-you-grow economics and low power and cooling with the performance, availability, and port densities of chassis-based platforms, the EX4300 enables businesses to deploy with speed and agility to increase revenue and improve productivity.

PRODUCT DESCRIPTION

The Juniper Networks® EX4300 line of Ethernet switches with Virtual Chassis technology combines the carrier-class reliability of modular systems with the economics and flexibility of stackable platforms, delivering a high-performance, scalable solution for data center, campus, and branch office environments. Both 1GbE access and multigigabit switch options are available.

Offering a full suite of Layer 2 and Layer 3 switching capabilities, the EX4300 enables a variety of deployments, including campus, branch, and data center access. A single 24-port or 48-port EX4300 switch can be deployed initially. As requirements grow, Juniper's Virtual Chassis technology allows any combination of up to 10 EX4300 and/or EX4600 switches to be seamlessly interconnected and managed as a single device, delivering a scalable, pay-as-you-grow solution for expanding network environments. A pair of 32-port EX4300 fiber switches can also be deployed as a consolidated aggregation or small core switch. Additionally, the EX4300 can integrate with the Juniper Networks QFX5100 line of 10GbE and 40GbE data center access switches in a single stack or Virtual Chassis configuration, enabling nondisruptive 10GbE server upgrades and simplified management of a mixed access environment.

The EX4300 switches can be interconnected over multiple 40GbE quad small form-factor pluggable plus (QSFP+) transceiver ports to form a 320 gigabit per second (Gbps) backplane. A flexible uplink module that supports both 1GbE and 10GbE options is also available, enabling high-speed connectivity to aggregation- or core-layer switches which connect multiple floors or buildings.

All EX4300 switches include high availability (HA) features such as redundant, hot-swappable internal power supplies and field-replaceable fans to ensure maximum uptime. In addition, Power over Ethernet (PoE)-enabled EX4300 switch models offer standards-based 802.3at PoE+ for delivering up to 30 watts on all ports to support high-density IP telephony and 802.11n wireless access point deployments.

Additionally, a multigigabit model, the EX4300-48MP, supports IEEE 802.3bz-compliant 100 Mbps, 1 Gbps, 2.5 Gbps, 5 Gbps, and 10 Gbps speeds on access ports. This enables 802.11ac Wave 2 access points, which require higher bandwidth, to connect to the switch. The EX4300 multigigabit switch also supports up to 95 watts of power on any of the access ports, enabling PoE++ devices requiring more than 30 watts to connect to and draw power from the switch.

The EX4300 multigigabit switch also enables higher levels of Media Access Control Security (MACsec) AES256 encryption on all access and uplink ports, protecting customer traffic from unauthorized access. The EX4300-48MP includes four dedicated 40GbE QSFP+ transceiver ports that can be used as Virtual Chassis ports to create a 320 Gbps backplane.

Chassis-Like Features in an Expandable Form Factor

The fixed-configuration EX4300 switches include a number of high availability features typically associated with chassis-based solutions, including the following:

- Hot-swappable fans
- Modular Juniper Networks Junos® operating system (consistent with chassis systems)
- Dual Routing Engines (REs) with graceful Routing Engine switchover (GRES) in a Virtual Chassis configuration
- Single management interface
- Easy, centralized software upgrades
- Scalability from 24 to 480 10/100/1000BASE-T ports and 24 to 240 100/1000/2500/5000/10000BASE-T ports, with up to 40 10GbE uplinks and 40 40GbE uplinks (up to 40 10GbE uplinks, 20 40GbE uplinks, or 20 100GbE uplinks on multigigabit models, in addition to four dedicated 40 Gbps Virtual Chassis ports per switch)

Each EX4300 switch includes a single ASIC-based Packet Forwarding Engine, the EX-PFE. The integrated Routing Engine (RE) delivers all control plane functionality. The EX4300 also leverages the same modular Junos OS as other Juniper Networks switches, routers, and security devices, ensuring a consistent implementation and operation of control plane features across the Juniper Networks infrastructure.

APPEARANCE

Figure 1. Juniper EX4300-48MP



Figure 2. Juniper EX4300-48P



Figure 3. Juniper EX4300-48T



Figure 4. Juniper EX4300-24P



Figure 5. Juniper EX4300-24T



Figure 6. Juniper EX4300-32F



Chassis-Class Availability

The EX4300 line of Ethernet switches delivers high availability through redundant power supplies and fans, GRES, and nonstop bridging and routing when deployed in a Virtual Chassis configuration.

In a Virtual Chassis configuration, each EX4300 switch is capable of functioning as a Routing Engine. When two or more EX4300 switches are interconnected, a single control plane is shared among all Virtual Chassis member switches. When two EX4300 switches are interconnected, Junos OS automatically initiates an election process to assign a master (active) and backup (hot-standby) RE. An integrated L2 and L3 GRES feature maintains uninterrupted access to applications, services, and IP communications in the unlikely event of a primary RE failure.

When more than two switches are interconnected in a Virtual Chassis configuration, the remaining switch elements act as line cards and are available to assume the backup RE position should the designated master fail. Master, backup, and line card priority status can be assigned to dictate the order of ascension; this N+1 RE redundancy, coupled with the GRES, nonstop routing (NSR), and nonstop bridging (NSB) capabilities of Junos OS, assures a smooth transfer of control plane functions following unexpected failures.

The EX4300 implements the same slot/module/port numbering schema as other Juniper Networks chassis-based products when numbering Virtual Chassis ports, providing true chassis-like operations. By using a consistent operating system and a single configuration file, all switches in a Virtual Chassis configuration are treated as a single device, simplifying overall system maintenance and management.

In a mixed Virtual Chassis configuration with both EX4300 1GbE access and multigigabit switches, the EX4300 multigigabit switches must assume the role of the RE, while the 1GbE access EX4300 switches can only act as line cards.

Individually, the EX4300 offers a number of HA features that are typically associated with modular chassis-based switches. When combined with the field-proven Junos OS and L2/L3 failover capabilities, these features provide the EX4300 with true carrier-class reliability.

- **Redundant power supplies:** The EX4300 line of Ethernet switches supports internal redundant, load-sharing, hot-swappable, and field-replaceable power supplies to maintain uninterrupted operations. Thanks to its compact footprint, the EX4300 requires significantly less power than

chassis-based switches delivering equivalent port densities. The EX4300 1GbE access switches offer both AC and DC options, while the EX4300 multigigabit switch supports only AC power supplies.

- **Hot-swappable fans:** The EX4300 includes hot-swappable fans, providing sufficient cooling even if one of the fans were to fail.
- **Nonstop bridging and nonstop routing:** NSB and NSR on the EX4300 ensure that control plane protocols, states, and tables are synchronized between master and standby REs to prevent protocol flaps or convergence issues following a Routing Engine failover.
- **Redundant trunk group (RTG):** To avoid the complexities of Spanning Tree Protocol (STP) without sacrificing network resiliency, the EX4300 employs redundant trunk groups to provide the necessary port redundancy and simplify switch configuration.
- **Cross-member link aggregation:** Cross-member link aggregation allows redundant link aggregation connections between devices in a single Virtual Chassis configuration, providing an additional level of reliability and availability.
- **Carrier-class hardware:** The EX4300 leverages a purpose-built packet forwarding engine ASIC, the EX-PFE, which integrates much of the same intellectual property used in Juniper's carrier-class routers. As a result, the EX4300 delivers the same predictable, scalable functionality found in the world's largest networks.
- **IPv4 and IPv6 routing support:** IPv4 and IPv6 Layer 3 routing (OSPF and BGP) is available with an Enhanced license, enabling highly resilient networks.

Carrier-Class Operating System

The EX4300 runs on Junos OS, the same operating system software used by other Juniper Networks switches, routers, and security devices.

By utilizing a common operating system, Juniper delivers a consistent implementation and operation of control plane features across all products. To maintain that consistency, Junos OS adheres to a highly disciplined development process that uses a single source code, follows a single quarterly release train, and employs a highly available modular architecture that prevents isolated failures from bringing an entire system down.

These attributes are fundamental to the core value of the software, enabling all products powered by Junos OS to be updated simultaneously with the same software release. All features are fully regression tested, making each new release a true superset of the previous version. Customers can

deploy the software with complete confidence that all existing capabilities will be maintained and operate in the same way.

Converged Networks

The EX4300 line of Ethernet switches provides the highest levels of availability for the most demanding converged data, voice, and video environments, delivering the most reliable platform for unifying enterprise communications.

The EX4300 supports rich quality of service (QoS) functionality for prioritizing data, voice, and video traffic. The switches support 12 QoS queues on every port, enabling them to maintain multilevel, end-to-end traffic prioritizations. The EX4300 also supports a wide range of policy options, including priority and weighted deficit round-robin (WDRR) queuing.

By providing 15.4 watts of Class 3 802.3af PoE on all ports to power voice over IP (VoIP) telephones, closed-circuit security cameras, wireless access points, and other IP-enabled devices, the EX4300 delivers a future-proofed solution for converging disparate networks onto a single IP infrastructure. The EX4300 switches also support standards-based 802.3at PoE+, which delivers up to 30 watts per port for powering networked devices such as multiple radio IEEE 802.11n wireless access points and video phones that may require more power than available with IEEE 802.3af. The EX4300 multigigabit switch supports pre-standard IEEE 802.3bt PoE++, which delivers up to 95 watts per port for powering devices requiring more than the 30 watts of power provided by PoE+.

Link Layer Discovery Protocol – Media Endpoint Discovery (LLDP-MED)-based granular PoE/PoE+ management allows the EX4300 to negotiate PoE/PoE+ usage down to a fraction of a watt on powered devices, enabling more efficient PoE utilization across the switch.

To ease deployment, the EX4300 supports the industry-standard LLDP and LLDP-MED, which enable the switches to automatically discover Ethernet-enabled devices, determine their power requirements, and assign virtual LAN (VLAN) parameters.

The EX4300 supports the IEEE 802.3az standard for Energy Efficient Ethernet (EEE) functionality, reducing power consumption of copper physical layers (PHY) during periods of low link utilization.

Security

The EX4300 provides a full complement of port security features, including Dynamic Host Configuration Protocol (DHCP) snooping, dynamic ARP inspection (DAI), IP source guard, and media access control (MAC) limiting (per port and per VLAN) to defend against internal and external spoofing, man-in-the-middle and denial-of-service (DoS) attacks.

MACsec

EX4300 switches support IEEE 802.1AE MACsec, providing support for link-layer data confidentiality, data integrity, and data origin authentication. The MACsec feature enables the EX4300 to support 88 Gbps of near line-rate hardware-based traffic encryption on all GbE and 10GbE ports, including the base unit and optional uplink modules. The multigigabit EX4300 model supports the MACsec AES 256 standard for encrypting traffic on all access and uplink ports.

Defined by IEEE 802.1AE, MACsec provides secure, encrypted communication at the link layer that is capable of identifying and preventing threats from denial of service (DoS) and intrusion attacks, as well as man-in-the-middle, masquerading, passive wiretapping, and playback attacks launched from behind the firewall. When MACsec is deployed on switch ports, all traffic is encrypted on the wire but traffic inside the switch is not. This allows the switch to apply all network policies such as QoS, deep packet inspection, and sFlow to each packet without compromising the security of packets on the wire.

Hop-by-hop encryption enables MACsec to secure communications while maintaining network intelligence. In addition, Ethernet-based WAN networks can use MACsec to provide link security over long haul connections. MACsec is transparent to Layer 3 and higher layer protocols and is not limited to IP traffic; it works with any type of wired or wireless traffic carried over Ethernet links.

Simplified Management and Operations

When employing Virtual Chassis technology, the EX4300 dramatically simplifies network management. Up to 10 interconnected EX4300 switches can be managed as a single device. Each Virtual Chassis group uses a single Junos OS image file and a single configuration file, reducing the overall number of units to monitor and manage. When Junos OS is upgraded on the master switch in a Virtual Chassis configuration, the software is automatically upgraded on all other member switches at the same time.

The EX4300 also includes port profiles that allow network administrators to automatically configure ports with security, QoS, and other parameters based on the type of device connected to the port. Six preconfigured profiles are available, including default, desktop, desktop plus IP phone, wireless access point, routed uplink, and L2 uplink. Users can select from the existing profiles or create their own and apply them through the command line interface (CLI), Junos Web interface, or management system.

The EX4300 switches can be managed through Junos Space® Network Director, a network management solution that allows users to visualize, analyze, and control the entire enterprise network—data center and campus, physical and virtual, wired and wireless—through a single pane of

glass. Network Director incorporates sophisticated analytics for real-time intelligence, trended monitoring, and automation to increase agility as well as faster rollout and activation of services.

For cloud deployments, Network Director provides a set of REST APIs that enable on-demand and dynamic network services by simplifying the consumption of services for multitenant environments. With third-party cloud orchestration tool integration, the Network Director API enables automation and provisioning of L2, L3, and security services in the data center without the need for manual operator intervention.

Finally, the EX4300 switch system, performance, and fault data can be exported to leading third-party management systems such as HP OpenView, IBM Tivoli, and Computer Associates Unicenter software to provide a complete, consolidated view of network operations.

Juniper Sky Enterprise

The EX4300 line is supported by Juniper Sky™ Enterprise, a cloud management solution that provides a “phone home” capability for branch devices, eliminating pre-staging and allowing the platforms to be managed from a central location. The simple yet flexible Juniper Sky Enterprise solution also supports other EX Series switches as well as standard SRX Series Services Gateways, allowing customization at the operations center.

PRODUCT OPTIONS

Ten EX4300 switch models are available (see Table 1 below).

Table 1. EX4300 Line of Ethernet Switches

Model/Product SKU	Access Port Configuration	PoE /PoE + Ports	PoE Budget	10GbE Ports (max. with module)	40GbE Ports (max. with module)	100GbE Ports (max. with module)	Power Supply Rating	Airflow
EX4300-24T	24-port 10/100/1000BASE-T	0	0 W	0 (4)	4	0	350 W AC	AFO (Front-to-back airflow)
EX4300-24P	24-port 10/100/1000BASE-T	24	550 W	0 (4)	4	0	715	AFO (Front-to-back airflow)

	T						W AC	ck airflow)
EX4300-48T	48-port 10/100/1000BASE-T	0	0 W	0 (4)	4	0	350 W AC	AFO (Front-to-back airflow)
EX4300-48P	48-port 10/100/1000BASE-T	48	900 W	0 (4)	4	0	1100 W AC	AFO (Front-to-back airflow)
EX4300-48T-AFI	48-port 10/100/1000BASE-T	0	0 W	0 (4)	4	0	350 W AC	AFI (Back-to-front airflow)
EX4300-48T-DC	48-port 10/100/1000BASE-T	0	0 W	0 (4)	4	0	550 W DC	AFO (Front-to-back airflow)
EX4300-48T-DC-AFI	48-port 10/100/1000BASE-T	0	0 W	0 (4)	4	0	550 W DC	AFI (Back-to-front airflow)
EX4300-48MP	24-port 10/100/1000BASE-T, 24-port 100/1000/2500/5000/ 10000BASE-T	48	1100	24 (28)	4* (2)	0 (2)	1400 W AC	AFO (Front-to-back airflow)
EX4300-32F	32-port 100/1000BASE-X	0	0 W	4 (12)	2 (4)	0	350 W AC	AFO (Front-to-back airflow)
EX4300-32F-DC	32-port 100/1000BASE-X	0	0 W	4 (12)	2 (4)	0	550 W DC	AFO (Front-to-back airflow)

*Dedicated Virtual Chassis ports cannot be used in Ethernet mode

The EX4300 also offers spare chassis options without power supplies or fans, providing customers with the flexibility to create custom SKUs. The supportability matrix for the EX4300 spare chassis SKUs is shown in Table 2. See Ordering Information section for registration details.

Table 2. Supportability Matrix for EX4300 Spare Chassis SKUs

Spare Chassis SKU	Description	PSU-350 -AC-AFO + EX4300-FAN	JPSU-7 15-AC-AFO + EX4300-FAN	JPSU-110 0-AC-AFO + EX4300-FAN	JPSU-140 0-AC-AFO + EX4300-FAN	JPSU-550 -DC-AFO + EX4300-FAN	JPSU-350 -AC-AFI+ EX4300-FAN-AFI	JPSU-550 -DC-AFI + EX4300-FAN-AFI
EX4300-48T-S	Spare chassis, 48-port 10/100/100 OBASE-T	P EX4300-48T	X	Y	X	P EX4300-48T-DC	P EX4300-48T-AFI	P EX4300-48T-DC-AFI
EX4300-48P-S	Spare chassis, 48-port 10/100/100 OBASE-T PoE+	Y	Y	P EX4300-48P	X	Y	Y	Y
EX4300-48MP-S	Spare chassis, 24-port 10/100/100 OBASE-T, 24-port 100/1000/2500/5000/10000BASE-T 95 W PoE	X	Y	Y	Y	X	X	X

EX4300-24T-S	Spare chassis, 24-port 10/100/100 0BASE-T	P EX4300-2 4T	X	Y	X	Y	Y	Y
EX4300-24P-S	Spare chassis, 24-port 10/100/100 0BASE-T PoE+	Y	P EX4300 -24P	Y	X	Y	Y	Y
EX4300-32F-S	Spare chassis, 32-port 100/1000B ASE-X SFP, 4x10GBASE -X SFP+, 2x40GBASE -X QSFP+	P EX4300-3 2F	X	Y	X	P EX4300-3 2F-DC	Y	Y

Note: P: supported as a SKU; Y: supported combination; X: unsupported combination

SPECIFICATIONS

Table 3. Specifications of Juniper EX4300 Switches

Physical Specifications	
Backplane	<ul style="list-style-type: none"> 320 Gbps Virtual Chassis interconnect to combine up to 10 units as a single logical device
Uplink Module Options	<ul style="list-style-type: none"> EX4300-32F/EX4300-32F-DC: 8-port dual-mode 10GbE/1GbE module with pluggable SFP+/SFP optics EX4300-32F/EX4300-32F-DC: 2-port dual-mode 40GbE module with pluggable QSFP+ optics

	<ul style="list-style-type: none"> EX4300-48MP: 4-port dual-mode 10GbE/1GbE module with pluggable SFP+/SFP optics or 2-port QSFP+/1-port QSFP28 module Others: 4-port dual-mode 10GbE/1GbE module with pluggable SFP+/SFP optics
Power Options	<ul style="list-style-type: none"> Power supplies: Autosensing; 100-120 V/200-240 V; AC 350 W AFO, 350 W AFI, 715 W AFO, and 1100 W AFO dual load-sharing hot-swappable internal redundant power supplies Maximum current inrush: 50 amps EX4300-48MP: 100-120 V/200-240 V; AC 715 W AFO, 1100 W AFO, 1400 W AFO dual load-sharing hot-swappable internal redundant power supplies DC power supply: 550 W DC AFO and 550 W DC AFI; input voltage range 43.5-60 V max (+/- 0.5 V); dual input feed, dual load-sharing hot-swappable internal redundant power supplies Minimum number of PSUs required for fully loaded chassis: 1 per switch
Dimensions (W x H x D)	<ul style="list-style-type: none"> EX4300 1GbE access models: 17.41 x 1.72 x 16.43 in. (44.21 x 4.32 x 41.73 cm) EX4300-48MP model: 17.4 x 1.7 x 18.4 in. (44.1 x 4.4 x 46.7 cm) Desktop installation width noted above, rack-mount width: 17.5 in, (44.5 cm) Height: 1 U
System Weight	<ul style="list-style-type: none"> EX4300 switch (with no power supply or fan module): 13 lb (5.9 kg) EX4300 switch (with single power supply and two fan modules): 16.1 lb (7.3 kg) 350 W AC power supply: 2.4 lb (1.1 kg) 715 W AC power supply: 2.4 lb (1.1 kg) 1100 W AC power supply: 2.4 lb (1.1 kg) 550 W DC power supply: 2.4 lb (1.1 kg) SFP+ uplink module: 0.44 lb (0.2 kg) Fan module: 0.33 lb (0.15 kg)
Environmental Ranges	<ul style="list-style-type: none"> Operating temperature: 32° to 113° F (0° to 45° C) Storage temperature: -40° to 158° F (-40° to 70° C) Operating altitude: up to 10,000 ft (3,049 m) Non-operating altitude: up to 16,000 ft (4,877 m) Relative humidity operating: 10% to 85% (noncondensing) Relative humidity non-operating: 0% to 95% (noncondensing)

Cooling	<ul style="list-style-type: none"> Field-replaceable fans: 2 Airflow: PSU-7.5 cubic feet per minute (CFM); fan-22 CFM Total maximum airflow throughput with two power supplies: 59 CFM
Hardware Specifications	
Switching Engine Mode	<ul style="list-style-type: none"> Store and forward
Memory	<ul style="list-style-type: none"> DRAM: 8 GB with Error Correcting Code (ECC) on EX4300-48MP, 3 GB with ECC on EX4300-32F and EX4300-32F-DC; 2 GB with ECC on all other EX4300 switches Flash: 64 GB on EX4300-48MP, 4 GB on EX4300-32F and EX4300-32F-DC; 2 GB on all other EX4300 switches
CPU	<ul style="list-style-type: none"> EX4300-48MP: 2.2 GHz Dual-Core Intel Broadwell CPU Other EX4300s: 1.5 GHz Dual-Core PowerPC CPU
GbE Port Density per System	<ul style="list-style-type: none"> 24P/24T: 32 (24 host ports + four 40GbE ports + optional four-port 1/10GbE uplink module) 32F: 46 (32 host ports + four 10GbE ports + two 40GbE ports + optional eight-port 1/10GbE uplink module or two-port 40GbE uplink module) 48P/48T/48MP: 56 (48 host ports + four 40GbE ports + optional four-port 1/10GbE uplink module) 10GbE port density per system: <ul style="list-style-type: none"> - 32F: 4 (fixed) + 8 (uplink module) - 48MP: 24 (fixed) = 4 (uplink module) - All others: 4 (uplink module) 40GbE port density per system: <ul style="list-style-type: none"> - 32F: 2 (fixed) + 2 (uplink module) - 48MP: 4 (fixed) + 2 (uplink module) - All others: 4 (fixed) 100GbE port density per system: <ul style="list-style-type: none"> -48MP: 2 (uplink module)
Supported Optics	<ul style="list-style-type: none"> GbE SFP optic/connector type: LC SFP fiber supporting SX (multimode), LX (single-mode) 10GbE SFP+ optic/connector type: 10GbE SFP+ LC connector, SR (multimode), USR (multimode), LR (single-mode), ER (single-mode), LRM (multimode), and DAC (direct-attach copper)

	<ul style="list-style-type: none"> • 40 GbE QSFP+ optic/connector type: 40GbE QSFP+ LC connector type, SR (multimode), DAC (direct-attach copper) • 100 GbE QSFP28 optic type: 100GbE QSFP SR4, LR4, DAC (direct-attach copper)
Physical Layer	<ul style="list-style-type: none"> • Time domain reflectometry (TDR) for detecting cable breaks and shorts: 24P/24T and 48P/48T only • Auto medium-dependent interface/medium-dependent interface crossover (MDI/MDIX) support: 24P/24T and 48P/48T/48MP only (all ports) • Port speed downshift/setting maximum advertised speed on 10/100/1000BASE-T ports: 24P/24T and 48P/48T/48MP only, on all ports • Digital optical monitoring for optical ports
Packet Switching Capacities (Maximum with 64 Byte Packets)	<ul style="list-style-type: none"> • 24P/24T: 448 Gbps • 48P/48T: 496 Gbps • 48MP: 960 Gbps • 32F: 464 Gbps
Software Specifications	
Security	<ul style="list-style-type: none"> • MAC limiting (per port and per VLAN) • Allowed MAC addresses configurable per port • Dynamic ARP inspection (DAI) • IP source guard • Local proxy ARP • Static ARP support • DHCP snooping • Captive portal • Persistent MAC address configurations • Distributed denial of service (DDoS) protection (CPU control path flooding protection)
Layer 2/Layer 3 Throughput (Mpps) (Maximum with 64 Byte Packets)	<ul style="list-style-type: none"> • EX4300-24P/24T: 333 Mpps (wire speed) • EX4300-48P/48T: 369 Mpps (wire speed) • EX4300-48MP: 714 Mpps • EX4300-32F: 345 Mpps (wire speed)
Layer 2 Switching	<ul style="list-style-type: none"> • Maximum MAC addresses per system: 64,000

- Jumbo frames: 9216 Bytes
- Number of VLANs supported: 4093
- Range of possible VLAN IDs: 1 to 4094
- Virtual Spanning Tree (VST) instances: 510
- Port-based VLAN
- Voice VLAN
- Physical port redundancy: Redundant trunk group (RTG)
- Compatible with Per-VLAN Spanning Tree Plus (PVST+)
- Routed VLAN Interface (RVI)
- Uplink Failure Detection (UFD)
- ITU-T G.8032: Ethernet Ring Protection Switching
- IEEE 802.1AB: Link Layer Discovery Protocol (LLDP)
- LLDP-MED with VoIP integration
- Default VLAN and multiple VLAN range support
- MAC learning disable
- Persistent MAC learning (sticky MAC)
- MAC notification
- Private VLANs (PVLANS)
- Explicit congestion notification (ECN)
- Layer 2 protocol tunneling (L2PT)
- IEEE 802.1ak: Multiple VLAN Registration Protocol (MVRP)
- IEEE 802.1p: CoS prioritization
- IEEE 802.1Q: VLAN tagging
- IEEE 802.1X: Port Access Control
- IEEE 802.1ak: Multiple Registration Protocol
- IEEE 802.3: 10BASE-T
- IEEE 802.3u: 100BASE-T
- IEEE 802.3ab: 1000BASE-T
- IEEE 802.3z: 1000BASE-X
- IEEE 802.3ae: 10-Gigabit Ethernet

	<ul style="list-style-type: none"> • IEEE 802.3ba: 40-Gigabit Ethernet • IEEE 802.3af: Power over Ethernet • IEEE 802.3at: Power over Ethernet Plus • IEEE 802.3x: Pause Frames/Flow Control • IEEE 802.3ah: Ethernet in the First Mile
Spanning Tree	<ul style="list-style-type: none"> • IEEE 802.1D: Spanning Tree Protocol • IEEE 802.1s: Multiple instances of Spanning Tree Protocol (MSTP) • Number of MST instances supported: 64 • Number of VLAN Spanning Tree Protocol (VSTP) instances supported: 510 • IEEE 802.1w: Rapid reconfiguration of Spanning Tree Protocol
Link Aggregation	<ul style="list-style-type: none"> • IEEE 802.3ad: Link Aggregation Control Protocol • 802.3ad (LACP) support: <ul style="list-style-type: none"> - Number of LAGs supported: 128 - Maximum number of ports per LAG: 16 • LAG load-sharing algorithm bridged or routed (unicast or multicast) traffic: <ul style="list-style-type: none"> - IP: S/D IP - TCP/UDP: S/D IP, S/D Port - Non-IP: S/D MAC • Tagged ports support in LAG
Layer 3 Features: IPv4	<ul style="list-style-type: none"> • Maximum number of ARP entries: 64,000 • Maximum number of IPv4 unicast routes in hardware: 16,000 prefixes; 32,000 host routes • Maximum number of IPv4 multicast routes in hardware: 8000 multicast groups; 16,000 multicast routes • Routing protocols: RIPv1/v2, OSPF, BGP, IS-IS • Static routing • Routing policy • Bidirectional Forwarding Detection (BFD) • L3 redundancy: Virtual Router Redundancy Protocol (VRRP)
Layer 3 Features: IPv6	<ul style="list-style-type: none"> • Maximum number of Neighbor Discovery (ND) entries: 32,000 • Maximum number of IPv6 unicast routes in hardware: 4000 prefixes; 15,000

	<p>host routes</p> <ul style="list-style-type: none"> ● Maximum number of IPv6 multicast routes in hardware: 8000 multicast groups; 16,000 multicast routes ● Routing protocols: RIPng, OSPFv3, IPv6, ISIS ● Static routing
<p>Access Control Lists (ACLs) (Junos OS Firewall Filters)</p>	<ul style="list-style-type: none"> ● Port-based ACL (PACL): Ingress and egress ● VLAN-based ACL (VACL): Ingress and egress ● Router-based ACL (RACL): Ingress and egress ● ACL entries (ACE) in hardware per system: <ul style="list-style-type: none"> - Port-based ACL (PACL) ingress: 3072 - VLAN-based ACL (VACL) ingress: 3500 - Router-based ACL (RACL) ingress: 7000 - Egress shared across PACL and VACL: 512 - Egress across RACL: 1024 - ACL counter for denied packets ● ACL counter for permitted packets ● Ability to add/remove/change ACL entries in middle of list (ACL editing) ● L2-L4 ACL
<p>Access Security</p>	<ul style="list-style-type: none"> ● 802.1X port-based ● 802.1X multiple supplicants ● 802.1X with VLAN assignment ● 802.1X with authentication bypass access (based on host MAC address) ● 802.1X with VoIP VLAN support ● 802.1X dynamic ACL based on RADIUS attributes ● 802.1X Supported Extensible Authentication Protocol (EAP types): Message Digest 5 (MD5), Transport Layer Security (TLS), Tunneled TLS (TTLS), Protected Extensible Authenticated Protocol (PEAP) ● MAC authentication (RADIUS) ● Control plane DoS protection ● Radius functionality over IPv6 for authentication, authorization, and accounting (AAA)

	<ul style="list-style-type: none"> • DHCPv6 snooping • IPv6 neighbor discovery • IPv6 source guard • IPv6 RA guard • IPv6 Neighbor Discovery Inspection • Media Access Control security (MACsec)
High Availability	<ul style="list-style-type: none"> • Redundant, hot-swappable power supplies • Redundant, field-replaceable, hot-swappable fans • Graceful Routing Engine switchover (GRES) for Layer 2 hitless forwarding and Layer 3 protocols on RE failover • Graceful protocol restart (OSPF, BGP) • Layer 2 hitless forwarding on RE failover • Nonstop bridging: LACP, xSTP • Nonstop routing: PIM, OSPF v2 and v3, RIP v2, RIPng, BGP, BGPv6, ISIS, IGMP v1, v2, v3 • Online insertion and removal (OIR) uplink module
Quality of Service	<ul style="list-style-type: none"> • L2 QoS • L3 QoS • Ingress policing: 1 rate 2 color • Hardware queues per port: 12 • Scheduling methods (egress): Strict priority (SP), WDRR • 802.1p, DiffCode (DSCP)/IP precedence trust and marking • L2-L4 classification criteria: Interface, MAC address, Ethertype, 802.1p, VLAN, IP address, DSCP/IP precedence, TCP/UDP port numbers, and more • Congestion avoidance capabilities: Tail drop, weighted random early detection (WRED)
Multicast	<ul style="list-style-type: none"> • IGMP: v1, v2, v3 • IGMP snooping • Multicast Listener Discovery (MLD) snooping • PIM-SM, PIM-SSM, PIM-DM
Services and Manageability	<ul style="list-style-type: none"> • Junos OS CLI

	<ul style="list-style-type: none"> ● Web interface ● Out-of-band management: Serial; 10/100/1000BASE-T Ethernet ● ASCII configuration ● Rescue configuration ● Configuration rollback ● Image rollback ● LCD management ● Element management tools: Juniper Networks Network and Security Manager (NSM) ● Remote performance monitoring ● Proactive services support via Advanced Insight Solutions (AIS) ● SNMP: v1, v2c, v3 ● RMON (RFC 2819) Groups 1, 2, 3, 9 ● Network Time Protocol (NTP) ● DHCP server ● DHCP client and DHCP proxy ● DHCP relay and helper ● DHCP local server support ● RADIUS ● Junos Space Service Now for automated fault detection, simplified trouble ticket management, and streamlined operations ● TACACS+ ● SSHv2 ● Secure copy ● HTTP/HTTPs ● Domain Name System (DNS) resolver ● System logging ● Temperature sensor ● Configuration backup via FTP/secure copy
MPLS	<ul style="list-style-type: none"> ● VRF-Lite
Supported RFCs	<ul style="list-style-type: none"> ● RFC 768 UDP

- RFC 783 TFTP
- RFC 791 IP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 Telnet client and server
- RFC 894 IP over Ethernet
- RFC 903 RARP
- RFC 906 TFTP Bootstrap
- RFC 951, 1542 BootP
- RFC 1027 Proxy ARP
- RFC 1058 RIP v1
- RFC 1112 IGMP v1
- RFC 1122 Host Requirements
- RFC 1195 Use of OSI IS-IS for Routing in TCP/IP and Dual Environments (TCP/IP transport only)
- RFC 1256 IPv4 ICMP Router Discovery (IRDP)
- RFC 1492 TACACS+RFC 1519 CIDR
- RFC 1587 OSPF NSSA Option
- RFC 1591 DNS
- RFC 1812 Requirements for IP Version 4 Routers
- RFC 1981 Path MTU Discovery for IPv6
- RFC 2030 SNTP, Simple Network Time Protocol
- RFC 2068 HTTP server
- RFC 2080 RIPng for IPv6
- RFC 2131 BOOTP/DHCP relay agent and DHCP server
- RFC 2138 RADIUS Authentication
- RFC 2139 RADIUS Accounting
- RFC 2154 OSPF w/Digital Signatures (password, MD-5)
- RFC 2236 IGMP v2
- RFC 2267 Network Ingress Filtering

- RFC 2328 OSPF v2 (edge-mode)
- RFC 2338 VRRP
- RFC 2362 PIM-SM (edge-mode)
- RFC 2370 OSPF Opaque LSA Option
- RFC 2453 RIP v2
- RFC 2460 Internet Protocol, Version 6 (IPv6) Specification
- RFC 2461 Neighbor Discovery for IP Version 6 (IPv6)
- RFC 2463 Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification
- RFC 2464 Transmission of IPv6 Packets over Ethernet Networks
- RFC 2474 DiffServ Precedence, including 12 queues/port
- RFC 2475 DiffServ Core and Edge Router Functions
- RFC 2526 Reserved IPv6 Subnet Anycast Addresses
- RFC 2597 DiffServ Assured Forwarding (AF)
- RFC 2598 DiffServ Expedited Forwarding (EF)
- RFC 2740 OSPF for IPv6
- RFC 2925 MIB for Remote Ping, Trace
- RFC 3176 sFlow
- RFC 3376 IGMP v3
- RFC 3484 Default Address Selection for Internet Protocol Version 6 (IPv6)
- RFC 3513 Internet Protocol Version 6 (IPv6) Addressing Architecture
- RFC 3569 draft-ietf-ssm-arch-06.txt PIM-SSM PIM Source Specific Multicast
- RFC 3579 RADIUS EAP support for 802.1x
- RFC 3618 Multicast Source Discovery Protocol (MSDP)
- RFC 3623 OSPF Graceful Restart
- RFC 4213 Basic Transition Mechanisms for IPv6 Hosts and Routers
- RFC 4291 IPv6 Addressing Architecture
- RFC 4443 ICMPv6 for the IPv6 Specification
- RFC 4541 IBMP and MLD snooping services
- RFC 4552 OSPFv3 Authentication
- RFC 4861 Neighbor Discovery for IPv6

	<ul style="list-style-type: none"> ● RFC 4862 IPv6 Stateless Address Autoconfiguration ● RFC 4915 MT-OSPF ● RFC 5095 Deprecation of Type 0 Routing Headers ● RFC 5176 Dynamic Authorization Extensions to RADIUS ● RFC 5798 VRRPv3 for IPv6 ● Draft-ietf-bfd-base-05.txt Bidirectional Forwarding Detection ● Draft-ietf-idr-restart-10.txt Graceful Restart Mechanism ● Draft-ietf-isis-restart-02 Restart Signaling for IS-IS ● Draft-ietf-isis-wg-multi-topology-11 Multi Topology (MT) Routing in IS-IS for BGP ● Internet draft-ietf-isis-ipv6-06.txt, Routing IPv6 with IS-IS ● LLDP Media Endpoint Discovery (LLDP-MED), ANSI/TIA-1057, draft 08 ● PIM-DM Draft IETF PIM Dense Mode draft-ietf-idmr-pim-dm-05.txt, draft-ietf-pim-dm-new-v2-04.txt
Supported MIBs	<ul style="list-style-type: none"> ● RFC 1155 SMI ● RFC 1157 SNMPv1 ● RFC 1212, RFC 1213, RFC 1215 MIB-II, Ethernet-Like MIB and TRAPs ● RFC 1493 Bridge MIB ● RFC 1643 Ethernet MIB ● RFC 1657 BGP-4 MIB ● RFC 1724 RIPv2 MIB ● RFC 1850 OSPFv2 MIB ● RFC 1905 RFC 1907 SNMP v2c, SMIv2 and Revised MIB-II ● RFC 2011 SNMPv2 for Internet Protocol using SMIv2 ● RFC 2012 SNMPv2 for transmission control protocol using SMIv2 ● RFC 2013 SNMPv2 for user datagram protocol using SMIv2 ● RFC 2096 IPv4 Forwarding Table MIB ● RFC 2287 System Application Packages MIB ● RFC 2570 – 2575 SNMPv3, user based security, encryption, and authentication ● RFC 2576 Coexistence between SNMP Version 1, Version 2, and Version 3 ● RFC 2578 SNMP Structure of Management Information MIB

	<ul style="list-style-type: none"> ● RFC 2579 SNMP Textual Conventions for SMlv2 ● RFC 2665 Ethernet-like interface MIB ● RFC 2787 VRRP MIB ● RFC 2819 RMON MIB ● RFC 2863 Interface Group MIB ● RFC 2863 Interface MIB ● RFC 2922 LLDP MIB ● RFC 2925 Ping/Traceroute MIB ● RFC 2932 IPv4 Multicast MIB ● RFC 3413 SNMP Application MIB ● RFC 3414 User-based Security model for SNMPv3 ● RFC 3415 View-based Access Control Model for SNMP ● RFC 3621 PoE-MIB (PoE switches only) ● RFC 4188 STP and Extensions MIB ● RFC 4363 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering, and VLAN extensions ● RFC 5643 OSPF v3 MIB support ● Draft - blumenthal - aes - usm - 08 ● Draft - reeder - snmpv3 - usm - 3desede -00 ● Draft-ietf-bfd-mib-02.txt ● Draft-ietf-idmr-igmp-mib-13 ● Draft-ietf-idmr-pim-mib-09 ● Draft-ietf-idr-bgp4-mibv2-02.txt - Enhanced BGP-4 MIB ● Draft-ietf-isis-wg-mib-07
Troubleshooting	<ul style="list-style-type: none"> ● Debugging: CLI via console, Telnet, or SSH ● Diagnostics: Show and debug command, statistics ● Traffic mirroring (port) ● Traffic mirroring (VLAN) ● IP tools: Extended ping and trace ● Juniper Networks commit and rollback
Traffic Monitoring	<ul style="list-style-type: none"> ● ACL-based mirroring

	<ul style="list-style-type: none"> ● Mirroring destination ports per system: 4 - LAG port monitoring - Multiple destination ports monitored to 1 mirror (N:1) ● Maximum number of mirroring sessions: 4 ● Mirroring to remote destination (over L2): 1 destination VLAN
Safety and Compliance	
Safety Certifications	<ul style="list-style-type: none"> ● UL-UL60950-1 (First Edition) ● C-UL to CAN/CSA 22.2 No. 60950-1 (First Edition) ● TUV/GS to EN 60950-1, Amendment A1-A4, A11 ● EN 60950-1 (2006 +A1:2009+A12:2010) Information Technology Equipment—Safety ● IEC 60950-1 (2005 +A1:2009) Information Technology Equipment—Safety
Electromagnetic Compatibility Certifications	<ul style="list-style-type: none"> ● FCC 47CFR Part 15 Class A ● EN 55022 Class A ● ICES-003 Class A ● VCCI Class A ● AS/NZS CISPR 22 Class A ● CISPR 22 Class A ● EN 55024 ● EN 300386 ● CE
NEBS	<ul style="list-style-type: none"> ● GR-1089-Core: EMC and Electrical Safety for Network Telecommunications Equipment
Environmental	<ul style="list-style-type: none"> ● Reduction of Hazardous Substances (ROHS) 6/6
Telco	<ul style="list-style-type: none"> ● CLEI code
Noise Specifications	<ul style="list-style-type: none"> ● Noise measurements based on operational tests taken from bystander position (front) and performed at 23° C in compliance with ISO 7779.

Table 4. EX4300 Power Supply Ratings and Acoustic Noise in dBA

Product	Power Supply Rating	Acoustic Noise
---------	---------------------	----------------

EX4300-24T	350 W AC AFO	38.5
EX4300-48T	350 W AC AFO	37.8
EX4300-48T-AFI	350 W AC AFI	38.9
EX4300-24P	715 W AC AFO	39.7
EX4300-48P	1100 W AC AFO	51.0
EX4300-48MP	1400 W AC AFO	53.7
EX4300-48T-DC	550 W DC AFO	39.7
EX4300-48T-DC-AFI	550 W DC AFI	39.7
EX4300-32F	350 W AC AFO	39
EX4300-32F-DC	550 W DC AFO	41.2

ORDERING INFORMATION

Table 5. Ordering information

Product number	Product description
Switches*	
EX4300-24T	24-port 10/100/1000BASE-T + 350 W AC PS (QSFP+ DAC for Virtual Chassis ordered separately)
EX4300-48T	48-port 10/100/1000BASE-T + 350 W AC PS (QSFP+ DAC for Virtual Chassis ordered separately)
EX4300-48T-AFI	48-port 10/100/1000BASE-T + 350 W AC PS (back-to-front airflow) (QSFP+ DAC for Virtual Chassis ordered separately)
EX4300-24P	24-port 10/100/1000BASE-T PoE-plus + 715 W AC PS (provides 565 W PoE+)

	power) (QSFP+ DAC for Virtual Chassis ordered separately)
EX4300-48P	48-port 10/100/1000BASE-T PoE-plus + 1100 W AC PS (provides 950 W PoE+ power) (QSFP+ DAC for Virtual Chassis ordered separately)
EX4300-48MP	24-port 10/100/1000BASE-T, 24-port 100/1000/2500/5000/10000BASE-T, 95 W PoE + 1400 W AC PS (provides up to 1100 W PoE++ power) (QSFP+ DAC for Virtual Chassis ordered separately)
EX4300-48T-DC	48-port 10/100/1000BASE-T + 550 W DC PS (QSFP+ DAC for Virtual Chassis ordered separately)
EX4300-48T-DC-AFI	48-port 10/100/1000BASE-T + 550 W DC PS (back-to-front airflow) (QSFP+ DAC for Virtual Chassis ordered separately)
EX4300-32F	32-port 100/1000BASE-X SFP, 4x10GBASE-X SFP+, 2x40GBASE-X QSFP+, and 350 W AC PS (optics sold separately)
EX4300-32F-DC	32-port 100/1000BASE-X SFP, 4x10GBASE-X SFP+, 2x40GBASE-X QSFP+, and 550 W DC PS (optics sold separately)
EX4300-24T-TAA	Trade Agreement Act-compliant EX4300, 24-port 10/100/1000BASE-T + 350 W AC PS (QSFP+ DAC for Virtual Chassis and optics ordered separately)
EX4300-48T-TAA	Trade Agreement Act-compliant EX4300, 48-port 10/100/1000BASE-T + 350 W AC PS (QSFP+ DAC for Virtual Chassis and optics ordered separately)
EX4300-48T-AFI-TAA	Trade Agreement Act-compliant EX4300, 48-port 10/100/1000BASE-T + 350 W AC PS (back-to-front airflow) (QSFP+ DAC for Virtual Chassis and optics ordered separately)
EX4300-48T-DC-TAA	Trade Agreement Act-compliant EX4300, 48-port 10/100/1000BASE-T + 550 W DC PS (QSFP+ DAC for Virtual Chassis and optics ordered separately)
EX4300-48T-DCI-TAA	Trade Agreement Act-compliant EX4300, 48-port 10/100/1000BASE-T + 550 W DC PS (back-to-front airflow) (QSFP+ DAC for Virtual Chassis and optics

	ordered separately)
EX4300-24P-TAA	Trade Agreement Act-compliant EX4300, 24-port 10/100/1000BASE-T PoE-plus + 715 W AC PS (provides 565 W PoE+ power) (QSFP+ DAC for Virtual Chassis and optics ordered separately)
EX4300-48P-TAA	Trade Agreement Act-compliant EX4300, 48-port 10/100/1000BASE-T PoE-plus + 1100 W AC PS (provides 950 W PoE+ power) (QSFP+ DAC for Virtual Chassis and optics ordered separately)
EX4300-32F-TAA	Trade Agreement Act-compliant EX4300, 32-port 100/1000BASE-X SFP, 4x10GBASE-X SFP+, 2x40GBASE-X QSFP+, and 350 W AC PS (optics sold separately)
EX4300-32F-DC-TAA	Trade Agreement Act-compliant EX4300, 32-port 100/1000BASE-X SFP, 4x10GBASE-X SFP+, 2x40GBASE-X QSFP+, and 550 W DC PS (optics sold separately)
Power Supplies	
JPSU-350-AC-AFO	EX4300 350 W AC power supply (power cord needs to be ordered separately) (front-to-back airflow)
Pluggable Optics	
QFX-QSFP-DAC-3M	QSFP+ to QSFP+ 40GbE Direct Attach Copper (twinax copper cable) 3 m passive

* Each switch ships standard with one power supply (including a power cord for the country to which it is being shipped), RJ-45 cable, RJ-45-to-DB-9 serial port adapter, and a 19 in. rack-mount kit. A second power supply is optional to provide resiliency. The appropriate power cord accompanying that power supply needs to be ordered separately. Virtual Chassis cables must be ordered separately and can be for any of the optics supported (40GbE DAC is recommended for Virtual Chassis connections).

WHERE TO BUY

Want to buy this series of products? please contact:

- Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com (Sales Inquiries)

Or visit: [Juniper EX4300 Series Ethernet Switches](#)

About us

Router-switch.com (HongKong Yejian Technologies Co., Ltd), founded in 2002, is one of the biggest Global Network Hardware Supplier. We are a leading provider of network products with 18,000+ customers in over 200 countries. We provide original new and used network equipments ([Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Juniper](#), EMC, etc.), including Routers, Switches, Servers, Storage, Telepresence and Videoconferencing, IP Phones, Firewalls, Wireless APs & Controllers, EHWIC/HWIC/VWIC Cards, SFPs, Memory & Flash, Hard Disk, Cables, and all kinds of network solutions related products.

SOURCES

<https://www.juniper.net/us/en/products-services/switching/ex-series/datasheets/1000467.page>